

# Liquid detector AFA 11

Class III, EN 13160-1/-4



- For storage rooms, manholes, collection facilities, etc.
- With visual/audible alarms
- Test/Acknowledge keys and relay output
- Self-monitoring probe
- Power outage alarm with optional battery
- EnOcean®-ready



**Application** For visual and audible alarms if liquids with a flash point of >55 °C are detected. AFA 11 is suitable for the following media: fuel oil, diesel fuel or low-viscosity lubricating oils, motor oils, gearbox oils or hydraulic oils, vegetable oils and transformer oils, water and other liquids. Application as leak detection system class III as per EN 13160-1/-4 as well as safety device as per worksheet DWA-A 791 and worksheet DWA-A779.

**Description** The unit in a wall mounting housing triggers visual and audible alarms in the event of accumulations of liquids which can be caused by leaks, backflow, flooding, etc. AFA 11 consists of a control unit with visual/audible alarm, test and acknowledge keys, a relay output and a photoelectric probe. The probe is mounted at the lowest point of the area to be monitored. Alarm is triggered when escaped liquid is detected. The audible alarm can be muted with the acknowledge key. The visual alarm remains active until the leak has been removed. The test key allows you to simulate an alarm condition in order to perform a function test. The voltage-free relay contact is provided for connection of additional alarm equipment (such as additional alarm unit ZAG 01, horn) or building control technology. The alarm units are suitable for panel mounting with a mounting frame.

Power outage alarm: An optional 9 V battery can be connected so that an audible alarm is triggered in the case of power outage. The alarm cannot be acknowledged and is disabled once power is available again.

EnOcean® ready: AFA 11 can be integrated into the AFRISO smart home system or other smart home systems based on EnOcean® wireless by means of the optional wireless module TCM 320. This allows for additional push messages to smartphones or via e-mail (further accessories required).

**Technical specifications**

**Operating temperature range**  
Ambient: -5/+40 °C

**Probe**  
L x Ø: 33 x 10 mm  
Cable length: 10 m

**Supply voltage**  
AC 100–240 V or AC/DC 15–24 V

**Switching output**  
Relay contact: 1 voltage-free changeover contact  
10 A, AC 250 V, DC 30 V

**Alarm sound**  
Min. 70 dB(A)

**Housing**  
Wall mounting housing made of impact-resistant plastic (ABS)  
W x H x D: 100 x 188 x 65 mm  
Degree of protection: IP 30 (EN 60529)

**Approval**  
DIBt: Z-65.40-214

**Scope of delivery**  
Control unit with probe

**Option**  
■ EnOcean® wireless module (can be retrofitted)

DG: G, PG: 4	Part no.
<b>Liquid detector AFA 11, AC 230 V</b>	<b>40890</b>
<b>Liquid detector AFA 11, 24 V</b>	40894
<b>Spare probe: photoelectric probe, 10 m</b>	<b>44503</b>
<b>EnOcean® wireless module TCM 320</b>	<b>78082</b>
<b>Mounting frame</b>	<b>43521</b>