




GasAlert Quattro

multi-gas detector



Visual auditing, easy compliance

Rugged and reliable, the GasAlertQuattro four-gas detector combines a comprehensive range of features with simple one-button operation. With flexible power options, the GasAlertQuattro is always ready. The graphic LCD displays easy to identify icons that indicate operational information, such as bump test and calibration status for simplified onsite auditing. IntelliFlash provides continuous visual confirmation of detector operation and compliance. Suited to a wide range of industrial applications including confined space entry, the GasAlertQuattro is fully compatible with BW's MicroDock II automatic test and calibration system.



Easy one-button operation



Always ready when you are



Simple, visual compliance

H₂S

CO

O₂

LEL

- Minimize costs and training with one-button operation
- Field-proven SureCell sensors offer an unprecedented performance in even the harshest environments
- Interchangeable power options with extended battery runtimes for longer shifts

**WATER
RESISTANT**



BW
Technologies
by Honeywell

Wear yellow. Work safe.

See[^]green.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor(s), battery status, circuit integrity and audible/visual alarms on start up and continuous testing on sensor(s)
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertQuattro Specifications

Size	5.1 x 3.2 x 1.9 in. / 13.0 x 8.1 x 4.7 cm	
Weight	- 11.15 oz. / 316 g (with rechargeable battery pack) - 11.92 oz. / 338 g (with alkaline battery pack)	
Temperature	-4 to +122°F / -20 to +50°C	
Humidity	10% - 100% RH (non-condensing)	
Alarms	- Visual (six red LEDs), vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)	
Tests	Sensor integrity, circuitry, battery and audible/visual alarms on activation, battery (continuous), sensor (continuous)	
Pump	Compatible with the Sampler motorized sampling pump	
Battery life	AA alkaline: 14 hrs (+68 to 122°F / +20 to 50°C) Rechargeable: 20 hrs (+68 to 122°F / +20 to 50°C) 18 hrs (-4 to +32°F / -20 to 0°C)	
User options	Confidence / compliance beep Confidence flash Set STEL interval Sensor on/off Latching alarms Safe display mode Force calibration Auto-zero on start up	Flip display Combustible gas measurement (% LEL or % by volume methane) User-definable calibration gas concentration Force bump Language choices (five) Custom start up message Datalog interval
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC IP66/IP67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D ATEX:  II 1 G Ga Ex ia IIC T4 IECEX: Ga Ex ia IIC T4  BR-Exia IIC T4	
Warranty	Full two-year warranty including all sensors	

* Patent pending

Additional GasAlertQuattro features:

- Powered by an interchangeable rechargeable battery pack or alkaline pack with 3 AA batteries
- One-button operation and straightforward user interface minimizes training
- Comprehensive datalogging and event logging capacity
- IntelliFlash verifies operation and compliance to both the user and supervisors from up to 20 ft. / 6.1 m
- Enhanced resistance to common industrial cross sensitive gases such as methanol and ethanol (CO and H₂S sensors)
- Multi-language support in English, French, German, Spanish and Portuguese
- Field-proven SureCell sensors offer an unprecedented performance in even the harshest environments.

Options and Accessories



MicroDock II compatible



Carrying holster



Auxiliary filter




Vehicle attachment

For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
Hydrogen sulfide (H₂S)	0-200 ppm	0.1 ppm
Carbon monoxide (CO)	0-1000 ppm	1 ppm
Oxygen (O₂)	0-30.0%	0.1%
Combustible gases (%LEL)	0-100% LEL 0-5.0% v/v	1% 0.1%
Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start up.		

Locally available from



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1.403.248.9226
Toll free: 1.800.663.4164

www.gasmonitors.com

USA 1.888.749.8878
Europe +44 (0)1295.700.300
France +33 (0) 442.98.17.70
Germany 49 (0) 2137.17.6522

info@gasmonitors.com

Middle East +971.4.887.1766
S.E. Asia +65.6580.3468
China +86.10.6786.7305
Australia +61.3.9464.2770

Latin America +55.11.3475.1873
Other Countries +1.403.248.9226

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

