

Questionnaire/Checklist for enquiries

Pressure gauges

Company:	Project/enquiry:
Quantity	
Application	
Medium to be measured	
Temperatures	T_{max} of medium: T_{max} ambient: T_{min} of medium: T_{min} ambient:
Pressure loads	Static: Dynamic: from to
Measuring system	<input type="checkbox"/> Bourdon tube element <input type="checkbox"/> Capsule element <input type="checkbox"/> Diaphragm M <input type="checkbox"/> Magnetic piston <input type="checkbox"/> Other: <input type="checkbox"/> Spring diaphragm
Housing diameter	<input type="checkbox"/> 40 <input type="checkbox"/> 50 <input type="checkbox"/> 63 <input type="checkbox"/> 80 <input type="checkbox"/> 100 <input type="checkbox"/> 160 <input type="checkbox"/> 250 mm <input type="checkbox"/> 4 1/2"
Range	
Connection	<input type="checkbox"/> Bottom <input type="checkbox"/> Back <input type="checkbox"/> Radial at ____ o'clock
Connection thread	<input type="checkbox"/> G <input type="checkbox"/> NPT <input type="checkbox"/> BSPT <input type="checkbox"/> 1/8 <input type="checkbox"/> 1/4 <input type="checkbox"/> 3/8 <input type="checkbox"/> 1/2 <input type="checkbox"/> 3/4 <input type="checkbox"/> Other:
Mounting type	<input type="checkbox"/> Direct <input type="checkbox"/> Back flange <input type="checkbox"/> Sheet steel, black <input type="checkbox"/> Stainless steel <input type="checkbox"/> 3-hole fixing panel <input type="checkbox"/> Black <input type="checkbox"/> Chrome plated <input type="checkbox"/> Stainless steel mounting bezel <input type="checkbox"/> 3-Panel mounting <input type="checkbox"/> Black <input type="checkbox"/> Chrome plated <input type="checkbox"/> Stainless steel bezel + clamp fixing
Housing	<input type="checkbox"/> Plastic <input type="checkbox"/> Sheet steel, black <input type="checkbox"/> Hot pressed brass <input type="checkbox"/> Stainless steel <input type="checkbox"/> Stainless steel with bayonet type bezel with clip-in front glass
Housing with blow-out	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Safety version S3
Filling	<input type="checkbox"/> Without <input type="checkbox"/> Glycerine <input type="checkbox"/> Silicone oil <input type="checkbox"/> Other:
Front glass	<input type="checkbox"/> Plastic <input type="checkbox"/> Instrument glass <input type="checkbox"/> Laminated safety glass Must be resistant to solvents <input type="checkbox"/> Yes <input type="checkbox"/> No Must be resistant to:
Wetted parts	<input type="checkbox"/> Brass <input type="checkbox"/> Steel <input type="checkbox"/> Stainless steel 1.4571 <input type="checkbox"/> Monel <input type="checkbox"/> Other:
Special coatings (diaphragm)	<input type="checkbox"/> PTFE <input type="checkbox"/> Other:
Measuring system helium tested	<input type="checkbox"/> Yes $qp_v = 10^{-6}$ <input type="checkbox"/> No
Dial	<input type="checkbox"/> Single scale as per EN <input type="checkbox"/> Dual scale: <input type="checkbox"/> Special scale: Customer's logo <input type="checkbox"/> Yes <input type="checkbox"/> No Manufacturer's logo <input type="checkbox"/> Yes <input type="checkbox"/> No
Accuracy class	<input type="checkbox"/> 0,1 <input type="checkbox"/> 0,25 <input type="checkbox"/> 0,6 <input type="checkbox"/> 1,0 <input type="checkbox"/> 1,6 <input type="checkbox"/> 2,5
Electrical contacts	<input type="checkbox"/> No <input type="checkbox"/> Magnetic spring contact <input type="checkbox"/> Inductive contact <input type="checkbox"/> Electronic contact <input type="checkbox"/> Single <input type="checkbox"/> Double <input type="checkbox"/> Triple <input type="checkbox"/> Quadruple Switching function:
Other	