## Questionnaire/Checklist for enquiries Thermometers

Company:	Project/enquiry:
Quantity	
Application	
Medium to be measured	
Version	☐ Bimetal thermometer ☐ Gas filled thermometer
Housing diameter	□ 34 □ 50 □ 63 □ 80 □ 100 □ 160 □ 250
Range	
Connection	☐ Bottom ☐ Back ☐ Rotatable or pivoted
Connection type	☐ Plain stem ☐ Loose male connection
	☐ Sep. screw-in thermowell ☐ Loose union nut
	☐ Sep. weld-in thermowell ☐ Compression fitting, adjustable
	☐ DIN/EN thermowell ☐ Fixed male connection
	Neck ☐ No
	☐ Yesmm
Connection thread	☐ G ☐ NPT ☐ BSPT ☐ For welding
	Other:
Stem length	
Mounting for capillary type	☐ Bracket for wall mounting ☐ Back flange
	☐ 3-hole fixing panel mounting bezel
Capillary length	
Housing	☐ Plastic ☐ Sheet steel
	☐ Stainless steel with push on bezel☐ Stainless steel with bayonet
	type bezel
Filling	☐ Without ☐ Glycerine ☐ Silicone oil ☐ Other:
Stem material	☐ Brass ☐ Stainless steel 1.4571/1.4541 ☐ Other:
Thermowell material	☐ Brass ☐ Steel ☐ Stainless steel
	☐ Other:
Dial	☐ Single scale as per EN ☐ Dual scale:
	☐ Special scale:
	Customer's logo ☐ Yes ☐ No Manufacturer's logo ☐ Yes ☐ No
Accuracy	Class ☐ 1 ☐ 2 According to EN 13190
Electrical contacts	□ No
(only for gas filled thermometers)	☐ Magnetic spring contact ☐ Inductive contact ☐ Electronic contact
	☐ Single ☐ Double ☐ Triple
	Switching function:
045	
Other	

