



1. ELECTRICAL SPECIFICATIONS

Accuracy calculated as $\pm[\% \text{reading} + (\text{num dgt} * \text{resolution})]$ ta 18°C ÷ 28°C, <75%RH

DC VOLTAGE

Range	Resolution	Accuracy	Input impedance	Overload protection
600.0mV	0.1mV	$\pm(0.1\% \text{rdg} + 5 \text{dgt})$	>10M Ω	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V	$\pm(0.2\% \text{rdg} + 5 \text{dgt})$		
1000V	1V			

AC TRMS VOLTAGE

Range	Resolution	Accuracy (*)		Overload protection
		(50Hz ÷ 60Hz)	(61Hz ÷ 1kHz)	
600.0mV	0.1mV	$\pm(0.9\% \text{rdg} + 5 \text{dgt})$	$\pm(3.0\% \text{rdg} + 5 \text{dgt})$	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

(*) Accuracy specified from 5% to 100% of measurement range, Input impedance: >10M Ω , Response time PEAK function: >1ms, Accuracy PEAK function: $\pm 10\% \text{rdg}$

AC+DC TRMS VOLTAGE

Range	Resolution	Accuracy (*) (50Hz ÷ 1kHz)	Input impedance	Overload protection
6.000V	0.001V	$\pm(3.0\% \text{rdg} + 20 \text{dgt})$	>10M Ω	1000VDC/ACrms
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

DC/AC TRMS WITH LOW IMPEDANCE (LoZ)

Range	Resolution	Accuracy (*) (50Hz ÷ 1kHz)	Input impedance	Overload protection
6.000V	0.001V	$\pm(3.0\% \text{rdg} + 20 \text{dgt})$	ca 3k Ω	1000VDC/ACrms
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

(*) Accuracy specified from 5% to 100% of measurement range
Fir not sinusoidal waveforms the accuracy is $\pm(10.0\% \text{rdg} + 10 \text{dgt})$

DC CURRENT

Range	Resolution	Accuracy	Overload protection
600.0 μ A	0.1 μ A	$\pm(0.9\% \text{rdg} + 5 \text{dgt})$	Fast Fuse 0.8A/1kVAC/DC (inputs mA, μ A)
6000 μ A	1 μ A		
60.00mA	0.01mA		
600.0mA	0.1mA	$\pm(0.9\% \text{rdg} + 8 \text{dgt})$	Fast Fuse 10A/1kVAC/DC (input 10A)
10.00A	0.01A	$\pm(1.5\% \text{rdg} + 8 \text{dgt})$	



AC TRMS CURRENT

Range	Resolution	Accuracy (*) (50Hz ÷ 1kHz)	Overload protection
600.0µA	0.1µA	±(1.2%rdg+5dgt)	Fast Fuse 0.8A/1kVAC/DC (inputs mA, µA)
6000µA	1µA		
60.00mA	0.01mA		
600.0mA	0.1mA		
10.00A	0.01A	±(1.5%rdg+5dgt)	Fast Fuse 10A/1kVAC/DC (input 10A)

(*)Accuracy specified from 5% to 100% of measurement range ; Response time PEAK function: >1ms, Accuracy PEAK function: ±10%rdg ; AC+DC TRMS Current: accuracy (50Hz÷1kHz): ±(3.0%rdg + 20dgt)

DC CURRENT WITH TRANSDUCER CLAMPS

Range	Output ratio	Resolution	Accuracy (*)	Overload protection
1000mA	1000mV/1000mA	1mA	±(1.5%rdg + 6dgt)	1000VDC/ACrms
10A	100mV/1A	0.01A		
30A			10mV/1A	
40A (**)	±(1.5%rdg + 26dgt) (***)			
100A	1mV/1A	1A	±(1.5%rdg + 6dgt)	
300A				
400A (**)	1mV/1A	1A	±(1.5%rdg + 26dgt) (***)	
1000A				

(*) Accuracy referred to only instrument without transducer ; (**) With HT4006 transducer clamp ; (***) Accuracy instrument + clamp

AC TRMS CURRENT WITH TRANSDUCER CLAMPS

Range	Output ratio	Resolution	Accuracy (*)	Overload protection
1000mA	1000mV/1000mA	1mA	±(2.5%rdg + 10dgt)	1000VDC/ACrms
10A	100mV/1A	0.01A		
30A			10mV/1A	
40A (**)	±(3.5%rdg + 30dgt) (***)			
100A	1mV/1A	1A	±(2.5%rdg + 10dgt)	
300A				
400A (**)	1mV/1A	1A	±(3.5%rdg + 30dgt) (***)	
1000A				
3000A				

(*) Accuracy referred to only instrument without transducer ; Accuracy specified from 5% to 100% of the measuring range;

(**) With HT4006 transducer clamp ; (***) Accuracy instrument + clamp

For not sinusoidal waveforms accuracy is: ±(10.0%reading + 10dgt)

Accuracy PEAK function: ±(10%rdg+30dgt) , AC+DC TRMS Current: accuracy (50Hz÷1kHz): ±(3.0%reading + 20dgt)

4-20mA% READINGS

Range	Resolution	Accuracy	Reading
-25% ÷ 125%	0.1%	±50dgt	0mA=-25%, 4mA=0%, 20mA=100%, 24mA=125%

DIODE TEST

Range	Max test current	Open voltage
	<1.5mA	3.2V

**RESISTANCE AND CONTINUITY TEST**

Range	Resolution	Accuracy	Buzzer	Overload protection
600.0Ω	0.1Ω	±(0.8%rdg+10dgt)	<50Ω	1000VDC/ACrms
6.000kΩ	0.001kΩ	±(0.8%rdg+5dgt)		
60.00kΩ	0.01kΩ			
600.0kΩ	0.1kΩ			
6.000MΩ	0.001MΩ			
60.00MΩ	0.01MΩ	±(2.5%rdg+10dgt)		

FREQUENCY (Electrical circuits)

Range	Resolution	Accuracy	Sensitivity	Overload protection
40Hz ÷ 10kHz	0.01Hz ÷ 0.001kHz	±(0.5%rdg)	2Vrms	1000VDC/ACrms

FREQUENCY (Electronic circuits)

Range	Resolution	Accuracy	Sensitivity	Overload protection
60.00Hz	0.01Hz	±(0.09%rdg+5dgt)	2Vrms min (20% < duty < 80%, <100kHz) 5Vrms min (20% < duty < 80%, >100kHz)	1000VDC/ACrms
600.0Hz	0.1Hz			
6.000kHz	0.001kHz			
60.00kHz	0.01kHz			
600.0kHz	0.1kHz			
1.000MHz	0.001MHz			

DUTY CYCLE

Range	Resolution	Accuracy	Overload protection
0.1 ÷ 99.9%	0.01%	±(1.2%rdg+2dgt)	1000VDC/ACrms

Pulse frequency range: 40Hz ÷ 10kHz, Pulse width: ±5V (100μs ÷ 100ms)

CAPACITANCE

Range	Resolution	Accuracy	Overload protection
60.00nF	0.01nF	±(1.5%rdg+20dgt)	1000VDC/ACrms
600.0nF	0.1nF	±(1.2%rdg+8dgt)	
6.000μF	0.001μF	±(1.5%rdg+8dgt)	
60.00μF	0.01μF	±(1.2%rdg+8dgt)	
600.0μF	0.1μF	±(1.5%rdg+8dgt)	
6.000mF	0.001mF	±(2.5%rdg+20dgt)	

TEMPERATURE WITH TYPE K PROBEK

Range	Resolution	Accuracy (*)	Overload protection
-40.0°C ÷ 600.0°C	0.1°C	±(1.5%rdg+3°C)	1000VDC/ACrms
600°C ÷ 1350°C	1°C		
-40.0°F ÷ 600.0°F	0.1°F	±(1.5%rdg+5.4°F)	
600°F ÷ 2462°F	1°F		

(*) Accuracy referred to instrument without probe



2. GENERAL SPECIFICATIONS

Display:

- TFT LCD, colours, 4½ dgt, 6000 counts, decimal point and bargraph
- Automatic polarity indication
- Backlight
- "OL" over range indication
- Response time: 3/s
- Conversion: TRMS

Features:

- Data HOLD
- MAX/MIN/AVG
- PEAK (Voltage and Current) ; AC+DC feature
- Data Logger and Graph of measured parameters
- Internal memory for measurements, graphs and recordings
- Icons internal menu
- REL
- DC 4-20mA% current readings

Memory:

- Measures: max 2000 snapshots; Graphs: max 50 ; Recordings: max 128 of 20000 points

Power supply:

- 1 x 7.2V Li-ION rechargeable battery
- Battery life: ca 15 hours
- Adapter battery charger: 100/240VAC, 50/60Hz, 10VDC, 1A
- Auto Power OFF programmable up to 60min of idleness

Environmental conditions:

- Operating Temperature/Humidity: 5°C ÷ 40°C, <80%RH
- Storage Temperature/Humidity: -20°C ÷ 60°C, <50%RH
- Altitude max of use: 2000m

Mechanica specifications

- Dimensions (L x W x H): 175 x 85 x 55mm
- Weight (included battery): 400g
- Mechanical protection: IP40

Reference guidelines:

- Safety : IEC/EN61010-1
- EMC : IEC/EN61326-1
- Pollution degree: 2
- Insulation: double insulation
- Measurement category: CAT IV 600V – CAT III 1000V

This product conforms to the prescriptions of the European directive on low voltage 2014/35/EU and to EMC directive 2014/30/EU

This product conforms to the prescriptions of the European directive 2011/65/EU (RoHS) and the European directive 2012/19/EU (WEEE)

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.



Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

