



1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as $\pm [\%rdg + (\text{numbers of digits} \times \text{resolution})]$ at $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$, $<80\%HR$

DC VOLTAGE

| Range | Resolution | Accuracy | Overload protection |
|----------|------------|-----------------------|---------------------|
| 100.00mV | 0.01mV | $\pm(0.08\%rdg+3dgt)$ | 1000VDC/ACrms |
| 1000.0mV | 0.1mV | $\pm(0.08\%rdg+2dgt)$ | |
| 10.000V | 0.001V | | |
| 100.00V | 0.01V | | |
| 1000.0V | 0.1V | | |

Input impedance: $10M\Omega // <100pF$

AC TRMS VOLTAGE

| Range | Resolution | Accuracy (50Hz ÷ 60Hz) | Accuracy (60Hz ÷ 5kHz) | Overload protection |
|----------|------------|---------------------------|---------------------------|---------------------|
| 100.00mV | 0.01mV | $\pm(0.9\%rdg+3dgt)$ | $\pm(0.9\%rdg+3dgt)$ | 1000VDC/ACrms |
| 1000.0mV | 0.1mV | | $\pm(1.9\%rdg+3dgt)$ | |
| 10.000V | 0.001V | | | |
| 100.00V | 0.01V | | | |
| 1000.0V | 0.1V | | $\pm(0.9\%rdg+3dgt) (*)$ | |

(*) In the range: 60Hz ÷ 1kHz

Input impedance: $10M\Omega // <100pF$

For non-sinusoidal voltages add the herewith correction on accuracies:

Crest factor: 1.4 ÷ 2.0 → add 1.0%rdg to the accuracy

Crest factor: 2.0 ÷ 2.5 → add 2.5%rdg to the accuracy

Crest factor: 2.5 ÷ 3.0 → add 4.0%rdg to the accuracy

AC TRMS VOLTAGE – Mode HFR

| Range | Resolution | Accuracy (50Hz ÷ 60Hz) | Accuracy (60Hz ÷ 5kHz) | Overload protection |
|---------|------------|---------------------------|---------------------------|---------------------|
| 10.000V | 0.001V | $\pm(0.9\%rdg+3dgt)$ | $\pm(2.9\%rdg+3dgt) (*)$ | 1000VDC/ACrms |
| 100.00V | 0.01V | | | |
| 1000.0V | 0.1V | | | |

(*) In the range: 60Hz ÷ 500Hz

Input impedance: $10M\Omega // <100pF$

Cutoff frequency mode HFR: 1kHz

For non-sinusoidal voltages consider the indication of AC TRMS voltage

DC CURRENT

| Range | Resolution | Accuracy | Overload protection |
|----------|------------|----------------------|---------------------|
| 100.00mA | 0.01mA | $\pm(0.2\%rdg+2dgt)$ | max 440mA |
| 400.0mA | 0.1mA | | |

AC TRMS CURRENT

| Range | Resolution | Accuracy (50Hz ÷ 5kHz) | Overload protection |
|----------|------------|---------------------------|---------------------|
| 100.00mA | 0.01mA | $\pm(1.5\%rdg+2dgt)$ | max 440mA |
| 400.0mA | 0.1mA | | |

For non-sinusoidal currents consider the indication of AC TRMS voltage



RESISTANCE

| Range | Resolution | Accuracy | Open voltage | Overload protection |
|----------|------------|-----------------|--------------|---------------------|
| 1000.0Ω | 0.1Ω | ±(0.5%rdg+2dgt) | approx 0.25V | 1000VDC/ACrms |
| 10.000kΩ | 0.001kΩ | | | |
| 100.00kΩ | 0.01kΩ | | | |
| 1000.0kΩ | 0.1kΩ | | | |
| 10.000MΩ | 0.001MΩ | | | |
| 40.00MΩ | 0.01MΩ | | | |

CONTINUITY TEST

| Range | Buzzer | Accuracy | Overload protection |
|--------|--------|-----------------|---------------------|
| 400.0Ω | <30Ω | ±(0.5%rdg+2dgt) | 1000VDC/ACrms |

Max open voltage: 1.2V

DIODE TEST

| Range | Accuracy | Open voltage | Overload protection |
|--------|-----------------|--------------|---------------------|
| 2.000V | ±(0.5%rdg+2dgt) | <2.5V | 1000VDC/ACrms |

Max test current: 0.6mA

FREQUENCY AC VOLTAGE/CURRENT

| Range | Resolution | Accuracy | Minumum pulse duration | Overload protection |
|-----------|------------|-----------------|------------------------|---------------------|
| 100.00Hz | 0.01Hz | ±(0.1%rdg+2dgt) | 10μs | 1000VDC/ACrms |
| 1000.0Hz | 0.1Hz | | | |
| 10.000kHz | 0.001kHz | | | |
| 100.00kHz | 0.01kHz | | | |

| Function | Range | Sensitivity (sinusoidal waveform) | |
|----------|----------|-----------------------------------|----------------|
| | | 10Hz ÷ 10kHz | 10kHz ÷ 100kHz |
| AC mV | 100.00mV | 15.00mV | |
| | 1000.0mV | 150.0mV | |
| AC V | 10.000V | 1.500V | |
| | 100.00V | 3V | - |
| | 1000.0V | 30V | - |
| AC mA | 100.00mA | 15.00mA | - |
| | 400.0mA | 30mA | - |

CAPACITANCE

| Range | Resolution | Accuracy | Meas. Time | Overload protection |
|----------|------------|------------------|------------|---------------------|
| 10.000nF | 0.001nF | ±(1.2%rdg+80dgt) | 0.7s | 1000VDC/ACrms |
| 100.00nF | 0.01nF | ±(1.2%rdg+20dgt) | | |
| 1000.0nF | 0.1nF | ±(1.2%rdg+2dgt) | | |
| 10.000μF | 0.001μF | | 3.75s | |
| 100.00μF | 0.01μF | | | |
| 1000.0μF | 0.1μF | ±(1.2%rdg+20dgt) | 7.5s | |
| 10.000mF | 0.001mF | ±(1.2%rdg+80dgt) | | |
| 40.00mF | 0.01mF | ±(1.2%rdg+80dgt) | | |



TEMPERATURE WITH TYPE K PROBE

| Range | Resolution | Accuracy | Overload protection |
|-------------------|------------|-----------------|---------------------|
| -200.0°C ÷ 0.0°C | 0.1°C | ±(1.0%rdg+2°C) | 1000VDC/ACrms |
| 0.0°C ÷ 1200.0°C | | ±(1.0%rdg+1°C) | |
| -328.0°F ÷ 32.0°F | 0.1°F | ±(1.0%rdg+36°F) | |
| 32.0°F ÷ 2192.0°F | | ±(1.0%rdg+18°F) | |

INSULATION RESISTANCE

| Test voltage | Measurement range | Accuracy | Overload protection |
|--------------|-------------------|-----------------|---------------------|
| 50V DC | 2.000MΩ | ±(1.5%rdg+5dgt) | 600VDC/ACrms |
| | 20.00MΩ | | |
| | 55.0MΩ | | |
| 100V DC | 2.000MΩ | | |
| | 20.00MΩ | | |
| | 110.0MΩ | | |
| 250V DC | 2.000MΩ | | |
| | 20.00MΩ | | |
| | 200.0MΩ | | |
| | 275MΩ | | |
| 500V DC | 2.000MΩ | | |
| | 20.00MΩ | | |
| | 200.0MΩ | | |
| | 550MΩ | | |
| 1000V DC | 2.000MΩ | | |
| | 20.00MΩ | | |
| | 200.0MΩ | | |
| | 2000MΩ | | |
| | 22.0GΩ | ±(10%rdg+3dgt) | |

Test voltage accuracy: +20%rdg, -0%rdg

Short-circuit current: 1mA

Minimum resistance (@ nominal current 1mA): 50kΩ (50V), 100kΩ (100V), 250kΩ (250V), 500kΩ (500V), 1MΩ (1000V)

Discharge time of measured object: <1s (C≤ 1μF)

Maximum capacitive load: 1μF

Voltage detection on circuit: test inhibited for voltages ≥30V AC/DC on inputs



2. GENERAL SPECIFICATIONS

Display:

- LCD display, 5 digit with maximum reading 10000 counts with sign, decimal point and bargraph
- Automatic polarity indication
- "OL" over range indication


Features:

- Data HOLD
- MAX/MIN/AVG for maximum, minimum and average values
- Auto Backlight for automatic activation of backlight
- LOCK for insulation measurement in continuous mode
- AUTOTEST for automatic detection of AC or DC measurements
- HFR for AC voltage measurement with 500Hz cut-off frequency
- SMOOTH for stability of insulation measurements
- Internal memory for saving/recall data
- RANGE for manual range selection
- REL for relative measurement (Resistance and Capacitance)
- Internal test on protection fuses
- Auto Power OFF after 20 minutes of idleness

Internal memory:

- Max 100 locations for each function

Low battery indication:

- The symbol  appears when the battery voltage is low

Environmental conditions:

- Working temperature/humidity: 0°C ÷ 50°C, <80%HR
- Storage temperature/humidity: -20°C ÷ 60°C, <80%HR

General information:

- Max height of use: 2000m
- Pollution degree: 2
- Insulation: double insulation

Power supply:

- 4 x 1.5V alkaline batteries type AA IEC LR6

Sizes:

- 207(L)x95(W)x52(H) mm

Weight (included batteries):

- 630g

Applied standards:

- Safety: IEC/EN61010-1, UL61010-1, IEC/EN61557-1, IEC/EN61557-2
- Measurement category: CAT IV 600V – CAT III 1000V

This product conforms to the prescriptions of the European directive on low voltage 2006/95/EEC and to EMC directive 2004/108/EEC

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.



Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

