

Perfection beyond limits.



## INFRARED THERMAL CAMERAS

Professional instruments  
for industrial, electrical and  
building applications.























Building the future since 1983

# Perfection beyond limits.

The range of **HT thermal imaging cameras**, supported by state-of-the-art technology, represents the unique and ideal solution for professionals in many sectors such as **industry, construction, maintenance and performance monitoring**, etc. The multiple pluses, from the large **touch screen display** to the **high IR resolution**, from the innovative **icon menu** to the **wide memory**, combined with the **extreme ease of use**, make HT thermal imaging cameras essential tools for accurate and professional thermographic analysis.

HT infrared cameras, the right and **perfect partner**.

						
Capacitive extra-bright touch screen	Interchangeable optional lenses	Laser pointer	Optical thermal camera in visible range	Integrated flash LED	Up to 3 independent cursors	Preset emissivity values of materials
						
Multi-areas with independent cursors	Fluid image on moving subjects	High resolution for detailed images	P.i.P. fusion Overlapping of visual and infrared images	PC USB 2.0 connection HDMI video output Data saving on MicroSD card	Use with the THTview*** App for iOS™ and Android™ systems	
						
Temperature range from -20 to +650 °C	Automatic SPAN adjustment	High thermal sensitivity	Rechargeable battery	IR video recording	Voice notes	Text notes

## THT70

ORDER CODE **HN000070**

ADVANCED INFRARED CAMERA WITH TOUCH SCREEN



WIFI CONNECTION

**BODY TEMPERATURE SCREENING**

**384x288**  
PIXEL


**RECHARGEABLE BATTERY**



SEE THE TECHNICAL DATA SHEET

- › UFPA IR sensor
- › Resolution: 384 x 288 pxl / 17µm
- › Temperature range: -20°C ÷ 650°C
- › Screening mode Temperature range: 32°C ÷ 42°C
- › Thermal sensitivity: <0.05°C @ 30°C / 50mK
- › Visual range: 17° x 12.7° (lens 22mm)
- › Image focusing: Manual on lens
- › Frequency: 50Hz

- › Colour palette: 8 Standard + 4 Isotherme lines
- › Camera type: 5Mpxl, FOV 59°
- › Display: 3.5" TFT colour display with capacitive touch-screen, high brightness
- › IR, Visual, Fusion PiP, Auto Fusion
- › Digital zoom: 1x ÷ 32x
- › Video output: HDMI
- › Duration: 3 hours



WIFI  
CONNECTION

**BODY  
TEMPERATURE  
SCREENING**

**160x120  
PIXEL**

**RECHARGEABLE  
BATTERY**



SEE THE  
TECHNICAL  
DATA SHEET

## THT60

ORDER CODE **HN000600**

ADVANCED INFRARED CAMERA  
WITH TOUCH SCREEN

- › Temperature range: -20°C ÷ 650°C
- › Screening mode temperature range: 32°C ÷ 42°C
- › UFPA IR sensor
- › Resolution: 160 x 120 pxl / 17µm
- › Thermal sensitivity: <0.05°C @ 30°C / 50mK
- › Visual range: 17.3° x 13° (lens 9mm)
- › Image focusing: Manual on lens
- › Frequency: 50Hz
- › Colour palettes: 8 standard + 4 isotherm lines
- › Camera type: 5Mpxl, FOV 59°
- › Display: 3.5" TFT colour display with capacitive touch-screen, high brightness
- › IR, Visual, Fusion PiP, Auto Fusion
- › Digital zoom: 1x ÷ 32x
- › Video output: HDMI
- › Duration: 3 hours



**BODY  
TEMPERATURE  
SCREENING**

**80x80  
PIXEL**

**RECHARGEABLE  
BATTERY**



SEE THE  
TECHNICAL  
DATA SHEET

## THT33

ORDER CODE **HN000033**

COMPACT INFRARED CAMERA

- › Temperature range: -20 ÷ 380°C
- › Screening mode temperature range: 32°C ÷ 42°C
- › Thermal sensitivity: < 0.1°C @ 30°C
- › Frequency: 50Hz
- › Visual range: 21° X 21°
- › 3 cursors: Central, Min, Max
- › Built-in white light lamp
- › Bluetooth connection to mobile devices
- › Duration: 5 hours
- › Calibration certificate ISO



**BODY  
TEMPERATURE  
SCREENING**

**160x120  
PIXEL**

**RECHARGEABLE  
BATTERY**



SEE THE  
TECHNICAL  
DATA SHEET

## THT46

ORDER CODE **HN000046**

COMPACT INFRARED CAMERA

- › Temperature range: -20°C ÷ 350°C
- › Screening mode temperature range: 32°C ÷ 42°C
- › Thermal sensitivity: < 0.1°C @ 30°C
- › Frequency: 50Hz
- › Visual range: 25° X 19°
- › Fusion PiP function
- › 3 cursors: Central, Min, Max
- › Laser pointer Class 2
- › Built-in white light lamp
- › Saving IR video and audio in MPEG4 format
- › USB port for PC connection and THTLink
- › Duration: 4 hours
- › Calibration certificate ISO



WIFI  
CONNECTION

**BODY  
TEMPERATURE  
SCREENING**

**80x80  
PIXEL**

**RECHARGEABLE  
BATTERY**



SEE THE  
TECHNICAL  
DATA SHEET

## THT45

ORDER CODE **HN000045**

COMPACT INFRARED CAMERA

- › Temperature range: -20°C ÷ 350°C
- › Screening mode temperature range: 32°C ÷ 42°C
- › Thermal sensitivity: < 0.1°C @ 30°C
- › Frequency: 50Hz
- › Visual range: 17° X 17°
- › Fusion PiP function
- › 3 cursors: Central, Min, Max
- › Laser pointer Class 2
- › Built-in white light lamp
- › Saving IR video and audio in MPEG4 format
- › USB port for PC connection and THTLink
- › WiFi connection to mobile devices
- › Duration: 4 hours
- › Calibration certificate ISO



COMPARISON CHART	THT70	THT60	THT46	THT45	THT33
IR Sensor resolution	384 x 288	160 x 120	160 x 120	80 x 80	80 x 80
Temperature range	-20 ÷ 650°C -4 ÷ 1202°F	-20 ÷ 650°C -4 ÷ 1202°F	-20 ÷ 350°C	-20 ÷ 350°C	- 20 ÷ 380°C
Thermal sensitivity	< 0.05°C @ 30°C	< 0.05°C @ 30°C	< 0.1°C @ 30°C	< 0.1°C @ 30°C	< 0.1°C @ 30°C
Frequency	50Hz	50Hz	50Hz	50Hz	50Hz
Visual range	17° X 12.7°	17.3° x 13°	25° X 19°	17° X 17°	21° X 21°
Advanced termographic analysis	•	•	-	-	-
Fusion PiP function for combining thermal and visual images	•	•	•	•	-
Cursors	4	4	3	3	3
Class 2 laser pointer	•	•	•	•	-
Integrated white light illuminator	•	•	•	•	•
Saving of IR videos and audio comments in MPEG4 format	•	•	•	•	-
USB connection and THTLink software	•	•	•	•	-
WiFi function for connection to mobile devices	• Wi-Fi	• Wi-Fi	-	• Wi-Fi	• Bluetooth
Duration	3 hours	3 hours	4 hours	4 hours	5 hours
Touchscreen display	•	•	-	-	-
ISO9000 Calibration certificate included	•	•	•	•	•
ORDER CODE	HN000070	HN000600	HN000046	HN000045	HN000033



**HT ITALIA S.R.L.**

Via della Boaria, 40 48018 Faenza (RA) Italia

T +39 0546 621002 | F +39 0546 621144 | M export@htitalia.it | ht-instruments.com



# Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



## KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

## Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

## EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

