

METRACABLE TDR PRO

Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

3-447-090-03
1/12.20

- Rugged, handy time domain reflectometer
- Measures cable length
- Pinpoints cable faults
- Identifies components (e.g. splitters)
- Provides information about the cabling itself (e.g. branches)
- Suitable for all types of electrical cables
- Long range of up to 14 km
- Memory function
- Internal cable database
- AUTO test function ensures readiness for operation at the touch of a button
- Freeze function for detailed viewing of the TDR trace
- Reference function for comparing two TDR traces at a glance
- METRACABLE MANAGER PC software included
- Data transfer to the PC via Bluetooth®



Applications

The METRACABLE TDR PRO is a compact, handy time domain reflectometer with a range of up to 14 km.

The METRACABLE TDR PRO is connected to the cable under test, to which it transmits a pulse. The pulse's reflection, i.e. its TDR trace, appears at the instrument's display panel.

Cable length is determined on the basis of the signal's reflection, whose shape also provides information concerning any included components (e.g. splitters), the cabling itself (e.g. splices, branches etc.) and any cable faults (short-circuits, broken cable, pinching etc.). The locations of components and faults are ascertained accurate to roughly 0.3 m.

Additional functions provide further support during cable inspection. The AUTO test function configures the most important parameters automatically and ensures that the instrument is quickly ready for operation. The freeze function permits detailed viewing of the TDR trace and the reference function saves the first of two measurements in the background, so that both can be compared at a glance.

The TDR trace display can be set up with either one or two cursors – one for absolute distance to the event and the other for measuring the distance between two events.

In combination with white background illumination, the extra high resolution of the high-contrast display ensures ideal viewing of the TDR trace in any environment.

Stored measurements can be conveniently transferred to the included METRACABLE MANAGER PC software via Bluetooth®. The software can be used to evaluate measurements and generate reports.

Features

- Rugged design
 - Impact-resistant ABS housing with fall protector
 - Protected display
 - Membrane keypad
- Compact, handy instrument
- Easy operation
- High-contrast display with background illumination
- High measuring resolution (localization accurate down to 0.3 m)
- BNC adapter for coaxial cable
- Surge protection
- METRACABLE MANAGER PC software
 - Data transfer via Bluetooth®
 - Measurement display
 - Report generation and printing
 - Cable database management
 - Instrument updates

METRACABLE TDR PRO

Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

Technical Data

Mechanical Design

Housing	Approx. 19.5 × 10.0 × 4.5 cm
Weight	Approx. 390 g (without batteries)
Protection	IP 52 per DIN VDE 0470, part 1/EN 60 529 (protection against ingress of solid foreign objects: ≥ 1.0 mm dia. Protection against water ingress: protection against falling dripping water, when the housing is inclined up to 15°)
Mechanical protection	Impact-resistant ABS housing with fall protector and display protection (2 mm Plexiglas with hardened safety glass)
Display	LCD, monochrome, luminous, 240 × 128 pixels, adjustable on-time and contrast for background illumina- tion
Connections	2 ea. 4mm banana plug safety sockets

Ambient Conditions

Operating temperature	-10 ... +50 °C
Storage temperature	-25 ... +75 °C
Relative humidity	No condensation allowed
Elevation	Max. 2000 m
Place of use	Indoors, in laboratories, in industrial environments, at construc- tion sites

Power Supply

Power Supply	4 ea. LR6 battery, 1.5 V, type AA or 4 ea. rechargeable NiMH, 1.2 V, type AA
Operating time	Up to 30 hours (depending on battery type and quality), adjustable automatic shutdown

Electrical Safety

Pollution degree	1
Protection class	II per DIN EN 61140/VDE 0140-1
Surge protection	DC: 100 V AC: 230 V / 50 Hz

Electromagnetic Compatibility

Interference emission	EN 55011: 2015
Interference immunity	EN 61000-4-2: 2009 EN 61000-4-3: 2006

Data

Interface	Bluetooth®
Internal Memory	Up to 32 entries in the cable database Up to 510 measurements in the instru- ment

Languages

Menu language	German, English, French
---------------	-------------------------

Measurements

Signal type	Symmetrical search signal
Range:	≤ 14 km
Accuracy	+1% ± pixels at 0.66 VF
Resolution	3.125 ns or 0.3 m depending on cable
Output pulse	Max. 20 V pp
Pulse lengths	12, 25, 50, 100, 200, 500, 1000 and 2500 ns
Velocity factor	Variable from 0.2 to 0.99 in steps of 0.01
Impedance	50, 75, 100, 125 Ω
Signal type	Symmetrical
Magnification factor	In steps of 6 dB

Cable Types

Suitable for	Symmetrical cables with maximum at- tenuation of 80 dB, for example: <ul style="list-style-type: none">– Coaxial cables– Shielded cables– Twisted pair cables– Multi-wire cables– Power cables
--------------	---

METRACABLE TDR PRO

Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

Scope of Delivery

- 1 METRACABLE TDR PRO (with carrying strap)
- 4 LR6 batteries, 1.5 V, type AA
- 1 Set of test probes (1.3 m, banana plugs, 300 V Cat II)
- 2 Alligator clips (plug-on)
- 1 BNC adapter (banana plug to coaxial cable)
- 1 Pouch (with carrying strap)
- 1 Condensed operating instructions

Order Information

Description	Type	Article No.
TDR measuring instrument including batteries, carrying strap, test probes, alligator clips, BNC adapter and pouch	METRACABLE TDR PRO	M281A

Further information regarding accessories can be found:

- In our Measuring Instruments and Testers catalog
- On the Internet at www.gossenmetrawatt.com



Included METRACABLE MANAGER PC software is available free of charge from our website at www.gossenmetrawatt.com.

© Gossen Metrawatt GmbH
Edited in Germany • Subject to change without notice / Errors excepted • A PDF version is available on the Internet

Alle Handelsmarken, eingetragenen Handelsmarken, Logos, Produktbezeichnungen und Firmennamen sind das Eigentum ihrer jeweiligen Besitzer.
All trademarks, registered trademarks, logos, product names and company names are the property of their respective owners.

 GOSSEN METRAWATT

Gossen Metrawatt GmbH
Südwestpark 15
90449 Nürnberg • Germany

Phone: +49 911 8602-111
Fax: +49 911 8602-777
e-mail: info@gossenmetrawatt.com
www.gossenmetrawatt.com

Les services d'EURO-INDEX

EURO-INDEX fournit des services pour tous les instruments de sa gamme de fournitures et offre des services, de la connaissance et du personnel hautement qualifié pour l'entretien (préventif), la réparation et le calibrage de vos instruments de mesure.

Centre de Service Agréé.....

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées.

Autrement dit, vos instruments sont traités par du personnel formé et compétent, qui dispose des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument ainsi que la certification (ATEX, EN50379, etc.) restent valables.

Laboratoire de maintenance et de calibrage

EURO-INDEX dispose d'un laboratoire de maintenance et de calibrage particulièrement moderne, titulaire d'une accréditation conforme à la norme NEN-EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105.



MQS®

MQS est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure. La prise en charge de multiples aspects vise à vous libérer de tout souci lors de l'utilisation de vos instruments de mesure. Les coûts sont modiques et prévisibles.

Accès numérique à vos certificats de calibrage avec Mon MQS

Mon MQS est un portail Web qui vous donne accès partout et à tout moment à vos certificats de calibrage et aux documents apparentés.

Location d'instruments de mesure

- Vaste assortiment
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires et leurs certificats de calibrage traçables

EURO-INDEX Academy

- Formations sur les produits (individuelles et collectives)
- Séminaires
- Vidéos de démonstration et d'instruction

Visionnez la vidéo sur notre chaîne YouTube et découvrez tout ce qu'il vous faut savoir sur MQS



Guichet des services



Calibrage de l'analyse de gaz de combustion



Séminaires et ateliers



Calibrage de la thermographie

Sous réserve de modifications EURO-INDEX® FR 18001

Le nom et la marque Bluetooth® sont la propriété de Bluetooth SIG Inc. L'utilisation de ce nom par EURO-INDEX s'effectue sous licence.



BELGIQUE
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

PAYS-BAS
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



Portée accréditée
voir www.rva.nl