

# METRACABLE TDR PRO

## Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

3-447-090-03  
1/12.20

- Rugged, handy time domain reflectometer
- Measures cable length
- Pinpoints cable faults
- Identifies components (e.g. splitters)
- Provides information about the cabling itself (e.g. branches)
- Suitable for all types of electrical cables
- Long range of up to 14 km
- Memory function
- Internal cable database
- AUTO test function ensures readiness for operation at the touch of a button
- Freeze function for detailed viewing of the TDR trace
- Reference function for comparing two TDR traces at a glance
- METRACABLE MANAGER PC software included
- Data transfer to the PC via Bluetooth®



### Applications

The METRACABLE TDR PRO is a compact, handy time domain reflectometer with a range of up to 14 km.

The METRACABLE TDR PRO is connected to the cable under test, to which it transmits a pulse. The pulse's reflection, i.e. its TDR trace, appears at the instrument's display panel.

Cable length is determined on the basis of the signal's reflection, whose shape also provides information concerning any included components (e.g. splitters), the cabling itself (e.g. splices, branches etc.) and any cable faults (short-circuits, broken cable, pinching etc.). The locations of components and faults are ascertained accurate to roughly 0.3 m.

Additional functions provide further support during cable inspection. The AUTO test function configures the most important parameters automatically and ensures that the instrument is quickly ready for operation. The freeze function permits detailed viewing of the TDR trace and the reference function saves the first of two measurements in the background, so that both can be compared at a glance.

The TDR trace display can be set up with either one or two cursors – one for absolute distance to the event and the other for measuring the distance between two events.

In combination with white background illumination, the extra high resolution of the high-contrast display ensures ideal viewing of the TDR trace in any environment.

Stored measurements can be conveniently transferred to the included METRACABLE MANAGER PC software via Bluetooth®. The software can be used to evaluate measurements and generate reports.

### Features

- Rugged design
  - Impact-resistant ABS housing with fall protector
  - Protected display
  - Membrane keypad
- Compact, handy instrument
- Easy operation
- High-contrast display with background illumination
- High measuring resolution (localization accurate down to 0.3 m)
- BNC adapter for coaxial cable
- Surge protection
- METRACABLE MANAGER PC software
  - Data transfer via Bluetooth®
  - Measurement display
  - Report generation and printing
  - Cable database management
  - Instrument updates

# METRACABLE TDR PRO

## Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

### Technical Data

#### Mechanical Design

Housing	Approx. 19.5 × 10.0 × 4.5 cm
Weight	Approx. 390 g (without batteries)
Protection	IP 52 per DIN VDE 0470, part 1/EN 60 529 (protection against ingress of solid foreign objects: ≥ 1.0 mm dia. Protection against water ingress: protection against falling dripping water, when the housing is inclined up to 15°)
Mechanical protection	Impact-resistant ABS housing with fall protector and display protection (2 mm Plexiglas with hardened safety glass)
Display	LCD, monochrome, luminous, 240 × 128 pixels, adjustable on-time and contrast for background illumina- tion
Connections	2 ea. 4mm banana plug safety sockets

#### Ambient Conditions

Operating temperature	-10 ... +50 °C
Storage temperature	-25 ... +75 °C
Relative humidity	No condensation allowed
Elevation	Max. 2000 m
Place of use	Indoors, in laboratories, in industrial environments, at construc- tion sites

#### Power Supply

Power Supply	4 ea. LR6 battery, 1.5 V, type AA or 4 ea. rechargeable NiMH, 1.2 V, type AA
Operating time	Up to 30 hours (depending on battery type and quality), adjustable automatic shutdown

#### Electrical Safety

Pollution degree	1
Protection class	II per DIN EN 61140/VDE 0140-1
Surge protection	DC: 100 V AC: 230 V / 50 Hz

#### Electromagnetic Compatibility

Interference emission	EN 55011: 2015
Interference immunity	EN 61000-4-2: 2009 EN 61000-4-3: 2006

#### Data

Interface	Bluetooth®
Internal Memory	Up to 32 entries in the cable database Up to 510 measurements in the instru- ment

#### Languages

Menu language	German, English, French
---------------	-------------------------

#### Measurements

Signal type	Symmetrical search signal
Range:	≤ 14 km
Accuracy	+1% ± pixels at 0.66 VF
Resolution	3.125 ns or 0.3 m depending on cable
Output pulse	Max. 20 V pp
Pulse lengths	12, 25, 50, 100, 200, 500, 1000 and 2500 ns
Velocity factor	Variable from 0.2 to 0.99 in steps of 0.01
Impedance	50, 75, 100, 125 Ω
Signal type	Symmetrical
Magnification factor	In steps of 6 dB

#### Cable Types

Suitable for	Symmetrical cables with maximum at- tenuation of 80 dB, for example: <ul style="list-style-type: none"><li>– Coaxial cables</li><li>– Shielded cables</li><li>– Twisted pair cables</li><li>– Multi-wire cables</li><li>– Power cables</li></ul>
--------------	---

# METRACABLE TDR PRO

## Time Domain Reflectometer – Cable Fault and Length Measuring Instrument

### Scope of Delivery

- 1 METRACABLE TDR PRO (with carrying strap)
- 4 LR6 batteries, 1.5 V, type AA
- 1 Set of test probes (1.3 m, banana plugs, 300 V Cat II)
- 2 Alligator clips (plug-on)
- 1 BNC adapter (banana plug to coaxial cable)
- 1 Pouch (with carrying strap)
- 1 Condensed operating instructions



### Order Information

Description	Type	Article No.
TDR measuring instrument including batteries, carrying strap, test probes, alligator clips, BNC adapter and pouch	METRACABLE TDR PRO	M281A

Further information regarding accessories can be found:

- In our Measuring Instruments and Testers catalog
- On the Internet at [www.gossenmetrawatt.com](http://www.gossenmetrawatt.com)

Included METRACABLE MANAGER PC software is available free of charge from our website at [www.gossenmetrawatt.com](http://www.gossenmetrawatt.com).

© Gossen Metrawatt GmbH  
Edited in Germany • Subject to change without notice / Errors excepted • A PDF version is available on the Internet

Alle Handelsmarken, eingetragenen Handelsmarken, Logos, Produktbezeichnungen und Firmennamen sind das Eigentum ihrer jeweiligen Besitzer.  
All trademarks, registered trademarks, logos, product names and company names are the property of their respective owners.

 GOSSEN METRAWATT

Gossen Metrawatt GmbH  
Südwestpark 15  
90449 Nürnberg • Germany

Phone: +49 911 8602-111  
Fax: +49 911 8602-777  
e-mail: [info@gossenmetrawatt.com](mailto:info@gossenmetrawatt.com)  
[www.gossenmetrawatt.com](http://www.gossenmetrawatt.com)

# Service van EURO-INDEX

**EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.**

## Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



## KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

## Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

## EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

**Bekijk de video op ons YouTube kanaal en ontdek alles over KWS**



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

