

# HONEYWELL

## Transmission Risk Air Monitor

A cost-effective monitor for use in schools, restaurants, and other small-to-medium-sized buildings that alerts users when conditions are present that may increase the risk of exposure to airborne viral transmission.\*

Classrooms, restaurants, and buildings with outdated HVAC and ventilation systems can foster environments where the risk of airborne virus transmission could increase.\* Honeywell proprietary technology that monitors CO<sub>2</sub> levels, coupled with user-controlled settings to account for human activity levels in an indoor area, provides users with a portable, cost- effective, and user-friendly solution that alerts when conditions are present that may increase the risk of exposure to airborne viral transmission.

Research conducted by scientists at the University of Colorado<sup>1</sup> has shown that real-time monitoring of indoor ambient air can be an indicator of increased risk of airborne viral transmission, utilizing different levels of risk-based factors such as CO<sub>2</sub> concentration levels and the type of human activity in the area.\*

Using this guidance and Honeywell algorithms, we identified air quality conditions that are driven by common activities and variables such as average room size, number of people present, breathing rate, and duration. The device comes with three pre-programmed indoor activity settings: low activity (movie theaters, libraries, and classrooms), medium activity (restaurants, offices, small clinics), and high activity (gyms, indoor arenas, recreation centers) and is recommended for coverage of 800-1000 square feet. For each setting, the monitor provides indications using a traffic light pattern (green, yellow, or red) and a sound alarm so users can be aware of conditions that may increase the risk of airborne transmission based on detectable CO<sub>2</sub> levels.



The Honeywell Transmission Risk Air Monitor helps you monitor indoor environments in real time for potential increase of exposure to airborne transmission risk.



Monitor exposure for students in classrooms to indicate transmission risk level.



Monitor airborne transmission risk levels in restaurants to alert of higher risk situations.

## FEATURES AND BENEFITS



The monitor comes with a user manual and USB charging cable. AC adapter sold separately.



Made of alloy and plastic, the monitor's sleek, lightweight design makes it easy to carry for real-time monitoring anywhere.



Red, yellow, and green indicators show at-a-glance the potential airborne transmission risk level of the air you are breathing.

**Honeywell**

# Honeywell Transmission Risk Air Monitor Technical Specifications

SPECIFICATIONS	
CHARACTERISTIC	PARAMETER
Dimensions (H × W × D)	80 mm × 80 mm × 22 mm [3.1 in × 3.1 in × 0.87 in]
Weight	150 g
Housing materials	Aluminum alloy
Display	TFT
Input voltage	5 V
Input current	1 A
Battery	Lithium-ion rechargeable battery 10-hour battery time
Battery capacity	2,600 mAh
Operating temperature & humidity	0°C to 50°C, 0% RH to 90% RH
USB port	Micro USB

SENSOR RANGE	
DESCRIPTION	DETECTION RANGE
CO <sub>2</sub> (NDIR)	400 ppm to 2000 ppm
Temperature	-20°C to 60°C or -4°F to 140°F
Humidity	0% RH to 100% RH

	GREEN	YELLOW	RED
<b>Conditions</b>	Likely low airborne transmission risk	Likely medium airborne transmission risk	Likely high airborne transmission risk
<b>Recommended Action</b>	–	<ul style="list-style-type: none"> <li>▪ Open windows</li> <li>▪ Turn on HVAC fan</li> </ul>	<ul style="list-style-type: none"> <li>▪ Ventilate room immediately</li> <li>▪ Reduce activities</li> <li>▪ Move out of room until light changes to green</li> </ul>
<b>Alarm</b>	–	One beep	Two beeps

In California's 2020 School Reopening Ventilation and Energy Efficiency Verification and Repair Program legislation, the importance of CO<sub>2</sub> monitoring in classroom settings is highlighted,

**"To ensure proper ventilation is maintained throughout the school year, all classrooms shall be equipped with a carbon dioxide monitor.<sup>2</sup>"**

<sup>1</sup> <https://tinyurl.com/FAQ-aerosols>

<sup>2</sup> [https://leginfo.legislature.ca.gov/faces/codes\\_displayText.xhtml?lawCode=PUC&division=1&title=&part=1.&chapter=8.7.&article=3](https://leginfo.legislature.ca.gov/faces/codes_displayText.xhtml?lawCode=PUC&division=1&title=&part=1.&chapter=8.7.&article=3)

Monitors should be placed in the center of activity areas and should be close to breathing height (approximately 1.5 m, depending on the height or age of the room occupants), out of direct sunlight, and not directly located near induction units, floor fans, or heaters.

\*The Honeywell Transmission Risk Air Monitor (HTRAM) analyzes specific air quality conditions and alerts the user when conditions are present that may increase the risk of exposure to airborne viral transmission. It does not prevent or reduce virus transmission nor mitigate viruses that may be present, nor does it detect or warn against the presence of any virus, including but not limited to COVID-19. The HTRAM does not repel or destroy any microorganism, viruses, bacteria, or germs.

- It is buyer's sole responsibility (1) to determine the suitability of the HTRAM for use in its application, (2) to operate the HTRAM in accordance with the user manual and any other instructions provided by Honeywell, (3) to determine, based on buyer's experience, expertise, and other available tools, the suitability of any product or service it may offer or recommend to the end user.
- Buyer is responsible for determining whether the product is appropriate for use under certain statutory guidelines and are likewise responsible for determining whether the HTRAM is subject to any government reimbursement programs.
- Any recommendations or assistance provided by Honeywell regarding the use or operation of the HTRAM – through our literature, the Honeywell web site, or otherwise – shall not be construed as representations or warranties of any kind, express or implied, and such information is accepted at buyer's own risk and without any obligation or liability to Honeywell.
- The information we supply in this data sheet is believed to be accurate and reliable as of this writing. However, specifications may change without notice, and Honeywell assumes no responsibility for its use.
- Honeywell disclaims all implied warranties, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, incidental, or indirect damages, or lost profits or lost revenues.



# Les services d'EURO-INDEX

**EURO-INDEX fournit des services pour tous les instruments de sa gamme de fournitures et offre des services, de la connaissance et du personnel hautement qualifié pour l'entretien (préventif), la réparation et le calibrage de vos instruments de mesure.**

## Centre de Service Agréé.....

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées.

Autrement dit, vos instruments sont traités par du personnel formé et compétent, qui dispose des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument ainsi que la certification (ATEX, EN50379, etc.) restent valables.

## Laboratoire de maintenance et de calibrage .....

EURO-INDEX dispose d'un laboratoire de maintenance et de calibrage particulièrement moderne, titulaire d'une accréditation conforme à la norme NEN-EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105.



## MQS® .....

MQS est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure. La prise en charge de multiples aspects vise à vous libérer de tout souci lors de l'utilisation de vos instruments de mesure. Les coûts sont modiques et prévisibles.

## Accès numérique à vos certificats de calibrage avec Mon MQS .....

Mon MQS est un portail Web qui vous donne accès partout et à tout moment à vos certificats de calibrage et aux documents apparentés.

## Location d'instruments de mesure .....

- Vaste assortiment
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires et leurs certificats de calibrage traçables

## EURO-INDEX Academy .....

- Formations sur les produits (individuelles et collectives)
- Séminaires
- Vidéos de démonstration et d'instruction

**Visionnez la vidéo sur notre chaîne YouTube et découvrez tout ce qu'il vous faut savoir sur MQS**



Guichet des services



Calibrage de l'analyse de gaz de combustion



Séminaires et ateliers



Calibrage de la thermographie

Sous réserve de modifications EURO-INDEX® FR 18001

Le nom et la marque Bluetooth® sont la propriété de Bluetooth SIG Inc. L'utilisation de ce nom par EURO-INDEX s'effectue sous licence.



BELGIQUE

Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
[info@euro-index.be](mailto:info@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)

PAYS-BAS

Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)



Portée accréditée  
voir [www.rva.nl](http://www.rva.nl)

