



1. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as [% rdg + (number of dgt) x resolution]. It is referred to 23°C ± 5°C, <80%RH

DC VOLTAGE

Range [V]	Resolution [V]	Accuracy	Input impedance	Overload protection
-1500.0 ÷ 1500.0	0.1	±(1.0%rdg + 3dgt)	1MΩ	1500VDC

Absolute voltage values <0.3V are zeroed

AC, AC+DC TRMS VOLTAGE

Range [V]	Resolution [V]	Accuracy	Input impedance	Overload protection
1.0 ÷ 999.9	0.1	±(1.0%rdg + 3dgt)	1MΩ	1000VDC/ACrms

Fundamental: 50/60Hz ± 15%, Bandwidth: 42.5Hz ÷ 1725Hz

Max. Crest Factor: 3 for voltage ≤470Vrms, 1.41 for voltage >470Vrms

Voltage RMS values <1V and values with frequency external range 42.5Hz ÷ 1725Hz are zeroed

DC VOLTAGE – MAX/MIN/CREST

Funzione	Range [V]	Resolution [V]	Accuracy	Response time
MAX/MIN	-1500.0 ÷ 1500.0	0.1	±(3.5%rdg + 5dgt)	200ms
CREST				1ms

Input impedance: 1MΩ ; Absolute voltage values <0.3V are zeroed

AC, AC+DC TRMS VOLTAGE – MAX/MIN/CREST

Funzione	Range [V]	Resolution [V]	Accuracy	Response time
MAX/MIN	1.0 ÷ 999.9	0.1	±(3.5%rdg + 5dgt)	200ms
CREST	-1500.0 ÷ 1500.0			1ms

Input impedance: 1MΩ; Fundamental: 50/60Hz ± 15%, Bandwidth: 42.5Hz ÷ 1725Hz

Max. Crest Factor: 3 for voltage ≤470Vrms, 1.41 for voltage >470Vrms

MAX/MIN values <1V, CREST values <1.4 and MAX/MIN/CREST values with frequency external range 42.5Hz ÷ 1725Hz are zeroed

DC CURRENT

Range [A]	Resolution [A]	Accuracy	Overload protection
0.1 ÷ 999.9	0.1	±(2.0%rdg + 5dgt)	1000ADC/ACrms

AC, AC+DC TRMS CURRENT

Range [A]	Resolution [A]	Accuracy	Overload protection
1.0 ÷ 999.9	0.1A	±(1.0%rdg + 5dgt)	1000ADC/ACrms

Fundamental: 50/60Hz ± 15%, Bandwidth: 42.5Hz ÷ 1725Hz ; Max. Crest Factor: 3 for current ≤515Arms, 1.41 for current >515A

Current RMS values <1A and values with frequency external range 42.5Hz ÷ 1725Hz are zeroed

DC/AC TRMS CURRENT – MAX/MIN

Range [A]	Resolution [A]	Accuracy	Response time	Overload protection
1.0 ÷ 999.9	0.1	±(3.5%rdg + 5dgt)	1s	1000VDC/ACrms

Fundamental: 50/60Hz ± 15%, Bandwidth: 42.5Hz ÷ 1725Hz ; Max. Crest Factor: 3 for current ≤515Arms, 1.41 for current >515A

MAX/MIN values <1A and MAX/MIN values with frequency external range 42.5Hz ÷ 1725Hz are zeroed

INRUSH CURRENT (DC, AC+DC TRMS) – DYNAMIC INRUSH

Range [A]	Resolution [A]	Accuracy (*)	Overload protection
1.0 ÷ 99.9	0.1	±(2.0%rdg + 5dgt)	1000ADC/ACrms
10 ÷ 999	1A		

(*) Accuracy declared for frequency: DC, (50±0.5)Hz, (60±0.5)Hz

Crest factor: 3, Sample frequency: 4kHz, Response time: Peak: 1ms, Max RMS : calculated on: 16.7, 20, 50, 100, 150, 200ms



HT9023

Rel. 1.01 of 06/07/20

DC/AC, AC+DC TRMS power clamp meter up to 1500VDC

Pag 2 of 4

RESISTANCE AND CONTINUITY TEST

Range [Ω]	Resolution [Ω]	Accuracy	Buzzer	Overload protection
0.0 ÷ 199.9	0.1	$\pm(1.0\%rdg + 5dgt)$	1 Ω ÷ 150 Ω	1000VDC/ACrms
200 ÷ 1999	1			
2.00k ÷ 19.99k	0.01k			
20.0k ÷ 29.9k	0.1k			

FREQUENCY WITH TEST LEADS AND JAWS

Range [Hz]	Resolution [Hz]	Accuracy	Overload protection
42.5 ÷ 69.0	0.1	$\pm(1.0\%rdg + 5dgt)$	1500VDC / 1000ADC/ACrms

Voltage range for frequency measure: 0.5 ÷ 1000V / Current range for frequency measure with jaws: 1 ÷ 1000A

PHASE SEQUENCE INDICATION AND PHASE CONFORMITY WITH 1-WIRE

Voltage range [V]	Frequency range [Hz]	Overload protection
100 ÷ 1000	45 ÷ 66	1000VDC/ACrms

Input impedance: 1.3M Ω

DC POWER

Range [kW]	Resolution [kW]	Accuracy (*)
0.00 ÷ 99.99	0.01	$\pm(3.0\%rdg + 3dgt)$
100.0 ÷ 999.9	0.1	

(*) Accuracy referred for Voltage > 10V, Current \geq 2A

AC, AC+DC ACTIVE, APPARENT POWER

Range [kW, kVA]	Resolution [kW, kVA]	Accuracy (*)
0.001 ÷ 9.999 (**)	0.001	$\pm(3.0\%rdg + 10dgt)$
10.00 ÷ 99.99	0.01	
100.0 ÷ 999.9	0.1	

(*) Accuracy referred for sinusoidal waveform, 42.5..69Hz, Voltage > 10V, Current \geq 10A, Pf \geq 0.5(**) For Current <10A add \pm 7%rdg to the accuracy

AC REACTIVE POWER

Range [kVAR]	Resolution [kVAR]	Accuracy (*)
0.001 ÷ 9.999 (**)	0.001	$\pm(3.0\%rdg + 10dgt)$
10.00 ÷ 99.99	0.01	
100.0 ÷ 999.9	0.1	

(*) Accuracy referred for sinusoidal waveform, 42.5..69Hz, Voltage > 10V, Current \geq 10A, Pf \leq 0.9(**) For Current <10A add \pm 4%rdg to the accuracy

AC, AC+DC TRMS AC ACTIVE ENERGY

Range [kWh]	Resolution [kWh]	Accuracy (*)
0.001 ÷ 9.999(**)	0.001	$\pm(3.0\%rdg + 10dgt)$
10.00 ÷ 99.99	0.01	
100.0 ÷ 999.9	0.1	

(*) Accuracy referred for sinusoidal waveform, 42.5..69Hz, Voltage > 10V, Current \geq 10A, Pf \geq 0.5(**) For Current <10A add \pm 7%rdg to the accuracy

AC, AC+DC TRMS AC REACTIVE ENERGY

Range [kVARh]	Resolution [kVARh]	Accuracy (*)
0.001 ÷ 9.999 (**)	0.001	$\pm(3.0\%rdg + 10dgt)$
10.00 ÷ 99.99	0.01	
100.0 ÷ 999.9	0.1	

(*) Accuracy referred for sinusoidal waveform, 42.5..69Hz, Voltage > 10V, Current \geq 10A, Pf \leq 0.9(**) For Current <10A add \pm 4%rdg to the accuracy



POWER FACTOR/ $\cos\phi$

Range	Resolution	Accuracy (*)
0.20i ÷ 1.00 ÷ 0.20c	0.01	$\pm(2.0\%rdg+2dgt)$

(*) Input impedance: 1M Ω , Accuracy referred for sinusoidal waveform, 42.5..69Hz, Voltage > 10V, Current \geq 2A

VOLTAGE / CURRENT HARMONICS

Harmonic order	Fund. frequency [Hz]	Resolution [V], [A]	Accuracy (* no zeroed values)
0 (DC)	42.5 ÷ 69.0	0.1V /0.1A	$\pm(10.0\%rdg+5dgt)$
1 ÷ 25			$\pm(5.0\%rdg+5dgt)$
THD%		0.1%	$\pm(10.0\%rdg+5dgt)$

(*) Voltage harmonics are zeroed in the below conditions:

- 1st harmonic: if value < 1.0V ; DC, 2nd to 25th harmonics: if harmonic value <0.5% of fundamental value or if value <1.0V

(*) Current harmonics are zeroed in the below conditions:

- 1st harmonic: if value <1.0A; DC, 2nd to 25th harmonics: if harmonic value <0.5% of fundamental value or if value <1.0A



2. GENERAL SPECIFICATIONS

General specifications

Aggregation time (IP):	1, 5, 10, 30, 60, 120, 300, 600 or 900s programmable
Inrush current acquiring threshold:	programmable between 2A ÷ 90A and 5A ÷ 900A in steps of 1A
Inrush current detection modes:	Fixed
Inrush current response times:	1ms (peak), 16.7,20,50,100,150,200ms (max RMS value)
Memory capacity:	2Mbytes
Interface to PC/mobile devices:	WiFi

Recordings/Autonomy

Inrush current snapshots saving:	max 20 (each with max 10 events)
Log + Snapshot saving:	max 99 files
Sampling rate:	128 sample/period (basic sample)
Max Rec autonomy (hours)	ca 2.1 x IP. e.g: IP=60s →ca126hours → ca 5days

Mechanical characteristics

Dimensions /L x W x H):	252 x 88 x 44mm
Weight (including battery):	420g
Max conductor size:	45mm
Mechanical protection:	IP20

Power supply

Battery type:	2 batteries 1.5V type AAA IEC LR03
Battery life:	approx. 40h (continue use in "W" position)
Auto Power Off:	approx. 5 minutes of idleness (disable)

Display

Characteristics:	graphic dot matrix, 128x128pxl with backlight
Sample rate:	128 samples/period (@ 50Hz)
Display update rate:	1 time/sec
Conversion mode:	TRMS

Climatic conditions

Reference temperature:	23°C ± 5°C
Operating temperature:	0°C ÷ 40 °C
Operating humidity:	<80%RH
Storage temperature:	-10°C ÷ 60°C
Storage humidity:	<70%RH
Max height of use:	2000m

Reference guidelines

Safety:	IEC/EN 61010-1, IEC/EN61010-2-032
EMC:	IEC/EN61326-1, EN301489-17V3.1.1, EN301328V2.1.1
Safety of test leads:	IEC/EN61010-031
Insulation:	double insulation
Pollution level :	2
Measurement category:	CAT IV 600V, CAT III 1000V to ground

This instrument satisfies the requirements of Low Voltage Directive 2014/35/EU (LVD) and of EMC Directive 2014/30/EU

This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.



Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

