



I-V600

Rel. 1.07 – 17/01/24

Professional I-V curve tracer up to 1500V, 40ADC

Pag 1 of 4

The **I-V600** model is an **I-V Curve** and functional test verification (Voc, Isc) instrument compliant with IEC/EN60891, IECEN60904-1-2 and IEC/EN62446 guidelines. **I-V600** tests the performance and functionality of **Monofacial** and **Bifacial** PV modules/strings.

I-V CURVE TRACER (PERFORMANCE/ACCEPTANCE TEST)

I-V600 verifies the performance of PV strings in compliance with IEC/EN60891 guideline by tracking the I-V curve on installations **up to 1500VDC and 40ADC**. Through solar irradiation and temperature measurements of the PV modules (in wireless combination with the **SOLAR03** remote unit), I-V600 extrapolates the @STC curves (**Standard Test Condition**: 1000W/m², 25°C, AM 1.5) comparing them with the ratings provided by the module manufacturer. The large internal database stores up to 1000 different manufacturers and up to 1000 modules associated with each manufacturer directly, easily programmable by touch-screen display.

FUNCTIONAL TEST (IVCK)

I-V600 verifies the functionality of PV strings in accordance with IEC/EN62446 guideline by measuring, with or without solar radiation, the open circuit voltage (Voc) and the short circuit current (Isc) in operating conditions (@OPC) **up to 1500VDC and 40ADC**. By measuring solar radiation and temperature of the PV modules (in wireless combination with the **SOLAR03** remote unit), I-V600 extrapolates the values @ STC (**Standard Test Condition**: 1000W/m², 25°C, AM 1.5) and compares them with the ratings provided by the module manufacturer.

I-V600 EXTENDS THE CHARGE OF THE INTERNAL BATTERIES

To increase the autonomy of the batteries and allow them to be recharged, I-V600 is equipped with a professional internal **BMS (Battery Management System)** algorithm which automatically recovers energy from the discharge of the module capacities at the end of an I-V test and from the voltage present on the inputs. A valid aid in case you need to carry out many tests in rapid succession.



HT ITALIA SRL
Via della Boaria, 40
48018 – Faenza (RA) – Italy
T +39 0546 621002 | F +39 0546 621144
M vendite@ht-instruments.com | ht-instruments.com

WHERE
WE ARE





I-V600

Rel. 1.07 – 17/01/24

Professional I-V curve tracer up to 1500V, 40ADC

Pag 2 of 4

1. ELECTRICAL SPECIFICATIONS

Accuracy calculated as $\pm[\% \text{reading} + (\text{number dgs} * \text{resolution})]$ at $23^\circ\text{C} \pm 5^\circ\text{C}$, <80%RH

DMM – Multimeter function – DC Voltage

Range [V]	Resolution [V]	Accuracy
3 ÷ 1500	1	$\pm(1.0\%\text{reading} + 2\text{dgt})$

I-V CURVE TEST

DC Voltage @ OPC

Range [V]	Resolution [V]	Accuracy (*)
15.0 ÷ 1500.0	0.1	$\pm(0.2\%\text{Voc})$

(*) In compliance with IEC/EN60904-1; The measurement starts if $\text{VDC} > 15\text{V}$ and module capacitance < $30\mu\text{F}$

DC Current @ OPC

Range [A]	Resolution [A]	Accuracy
0.20 ÷ 40.00	0.01	$\pm(0.2\%\text{isc})$

(*) In compliance with IEC/EN60904-1; $\text{Iscmin} = 0.2\text{A}$ and module capacitance < $30\mu\text{F}$

DC Power @ OPC (VDC > 30V)

Range [W]	Resolution [W]	Accuracy
50 ÷ 9999	1	$\pm(1.0\%\text{reading}+6\text{dgt})$
10.00k ÷ 59.99k	0.01k	

$\text{VDC Voltage} \geq 30\text{V}$ and module capacitance < $30\mu\text{F}$

DC Voltage @ STC

Range [V]	Resolution [V]	Accuracy
3.0 ÷ 1500.0	0.1	$\pm(4.0\%\text{reading}+2\text{dgt})$

DC Current @ STC

Range [A]	Resolution [A]	Accuracy
0.20 ÷ 40.00	0.01	$\pm(4.0\%\text{reading}+2\text{dgt})$

DC Power @ STC (referred @ 1 module)

Range [W]	Resolution [W]	Accuracy
50 ÷ 9999	1	$\pm(4.0\%\text{reading}+2\text{dgt})$





I-V600

Rel. 1.07 – 17/01/24

Professional I-V curve tracer up to 1500V, 40ADC

Pag 3 of 4

FUNCTIONAL TEST (IVCK)

DC Voltage @ OPC

Range [V]	Resolution [V]	Accuracy (*)
15.0 ÷ 1500.0	0.1	±(0.2%Voc)

(*) In compliance with IEC/EN60904-1; The measurement starts if VDC > 15V and module capacitance <30µF

DC Current @ OPC

Range [A]	Resolution [A]	Accuracy (*)
0.20 ÷ 40.00	0.01	±(0.2%isc)

(*) In compliance with IEC/EN60904-1; Iscmin = 0.2A and module capacitance <30µF

DC Voltage @ STC

Range [V]	Resolution [V]	Accuracy
3.0 ÷ 1500.0	0.1	±(4.0%reading+2dgts)

DC Current @ STC

Range [A]	Resolution [A]	Accuracy
0.20 ÷ 40.00	0.01	±(4.0%reading+2dgts)





2. GENERAL SPECIFICATIONS

DISPLAY AND MEMORY

Characteristics:	Color TFT, capacitive touch screen, 7", 800x480pxl
Type of memory:	Memory card, max 32GB (not expandable)
Module database:	ca. 63,000 saved modules
Storable data:	9999 test IVCK or I-V curve

POWER SUPPLY:

Internal power supply:	8x1.5V alkaline battery type LR6, AA or 8x1.2V rechargeable battery NiMH type LR6, AA
External power supply:	100-440VAC/15VDC, 50/60Hz CAT IV 300V (use only HT adapter) via inputs P1, C1, P2, C2
Battery charging algorithm:	energy recovered from I-V curve measurements
Battery charging system (BMS):	8W
Consumption:	" symbol shown on the display
Low battery indication:	approx. 4 hours
Charging time:	8 hours in the following conditions: ➤ Battery capacity: 2000mAh ➤ PV string voltage: 800V ➤ Work cycles: 80 measurements/hour ➤ Instrument connected to the modules for 30s/measurement ➤ Instrument disconnected for 15s/measurement
Battery life (@ 0°C ÷ 40°C):	1 ÷ 10min selectable (disabling)
Auto Power OFF:	

OUTPUT INTERFACE

PC interface:	USB-C and WiFi
Interface with SOLAR03:	Bluetooth connection (up to 100m in free space)

MECHANICAL CHARACTERISTICS

Dimensions (L x W x H):	336 x 300 x 132mm (13 x 12 x 5in)
Weight (included batteries):	5.5kg (11lb)
Mechanical protection:	IP40 (open case), IP67 (closed case)

ENVIRONMENTAL CONDITIONS OF USE

Reference temperature:	23°C ± 5°C (73°F ± 41°F)
Operating temperature:	-10°C ÷ 50°C (14°F ÷ 122°F)
Operating humidity:	<80%RH
Storage temperature:	-20°C ÷ 60°C (-4°F ÷ 140°F)
Storage humidity:	<80%RH
Max. height of use:	2000m (6562ft)

REFERENCE GUIDELINES

Safety:	IEC/EN61010-1, IEC/EN61010-2-030,
EMC:	IEC/EN61326-1
Safety measurement accessories:	IEC/EN61010-031
I-V Test:	IEC/EN60891, IECEN60904-1-2
IVCK Test:	IEC/EN62446, IECEN60904-1-2
Insulation:	double insulation
Pollution degree:	2
Radio:	ETSI EN300328, ETSIEN301489-1, ETSIEN301489-17
Measurement category:	CAT III 1500VDC, max 1500VDC between inputs

This instrument complies with the requirements of the European Low Voltage Directive 2014/35/EU (LVD), the Directive 2014/30/EU (EMC) and the RED regulation 2014/53/EU

This instrument complies with the requirements of the European Directive 2011/65/EU (RoHS) and the European Directive 2012/19/EU (WEEE)



Services d'EURO-INDEX

EURO-INDEX est un fabricant, importateur et distributeur de diverses marques A dans le domaine des instruments de test et de mesure. Nous fournissons également une large gamme de services pour optimiser l'utilisation de ces instruments dans vos activités. Ces services comprennent naturellement l'entretien, la réparation et l'étalonnage des instruments, mais nous proposons aussi une assistance sous forme de formation via notre EURO-INDEX Academy et la location d'instruments.

Centre de Service Agréé

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées. Cela signifie que vos instruments sont pris en charge par des techniciens formés par le fabricant et disposant des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument, ainsi que les certifications (ATEX, EN50379, etc.) restent intactes.



Laboratoire de maintenance et de calibrage

Le laboratoire des Pays-Bas est accrédité RvA selon la norme EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105. Les certificats de calibrage RvA sont acceptés à l'international et équivalents à ceux de BELAC.



Service Mobile

Outre les laboratoires d'étalonnage fixes de Zaventem et de Capelle aan den IJssel, nous disposons également d'un laboratoire itinérant appelé "Service mobile". Nos services puissent venir vers vous, en offrant une qualité équivalente.

MQS®

MQS® est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure à un coût fixe et faible. Via un portail Web gratuit (monmqs.be), vous avez toujours accès à vos certificats de calibrage.

Location d'instruments de mesure

- Vaste assortiment
- Précision démontrable par le certificat d'étalonnage actuel
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires

EURO-INDEX Academy

- Formations et séminars
- Vidéos de démonstration et d'instruction
- Notes d'application



Comptoir de service



Entretien, réparation et calibrage



Formations et séminars



Service Mobile

Sous réserve de modifications EURO-INDEX® FR 23001



BELGIQUE

Chaussée de Louvain 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

PAYS-BAS

Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

