



PQA924

CLASS S
POWER QUALITY ANALYZER



ORDER CODE **HV000924**

PQA924

CLASS S
POWER QUALITY ANALYZER



HT**Agorà**

→ **TRMS**

- › AC voltage in single-phase and three-phase systems
- › AC current in single-phase and three-phase systems
- › Cosphi, Power Factor, K-Factor
- › Voltage unbalance
- › Flicker
- › Active, Reactive, and Apparent power/energy
- › Voltage and current harmonic amplitude and phase up to the 63rd order with THD% calculation
- › Power harmonic amplitude up to the 63rd order
- › Voltage and current interharmonics up to the 63rd order with THI% calculation
- › Voltage anomalies (dips, swells) with 10ms resolution (@50Hz)
- › Fast voltage transients (8kV, 1μs)
- › Inrush current for electric motors
- › Event waveform recording (anomalies, fast transients, and inrush currents)
- › Phase sequence detection
- › Data transfer to PC via HTAgorà software
- › Up to **3180** simultaneously recordable electrical parameters with programmable integration period
- › USB, Ethernet, and Wi-Fi connection
- › Memory card
- › Color touchscreen display



**SEE PRODUCT
DATA SHEET**

Maximum accuracy and reliability with the auto-configuration (AUTOSSET) function

The PQA924 features an advanced auto-configuration function designed to eliminate connection errors and optimize setup time. Thanks to the Autoset mode, the operator can ensure the correct assignment of clamp sensors, preventing incorrect measurements and discrepancies in the recorded electrical values.

4 key reasons to use the AUTOSSET function

- › Automatically detects the connected current transducers for immediate, error-free configuration.
- › Prevents wiring errors that could compromise measurement accuracy.
- › Avoids inconsistent electrical values and the need to repeat recordings.
- › Automatically corrects reversed current clamps on conductors, preventing misalignment between voltage and current that could result in incorrect readings.



TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

AC voltage in single-phase and three-phase systems	●
AC current in single-phase and three-phase systems	●
Cosphi, Power Factor, K-Factor	●
Voltage unbalance	●
Flicker	●
Active, Reactive, Apparent power/energy	●
Voltage and current harmonic amplitude and phase up to the 63 rd order with THD% calculation	●
Power harmonic amplitude up to the 63 rd order	●
Voltage and current interharmonics up to the 63 rd order with THI% calculation	●
Voltage anomalies (dips, swells) with 10ms resolution (@50Hz)	●
Fast voltage transients (8kV, 1μs)	●
Inrush current for electric motors	●
Event waveform recording (anomalies, fast transients, and inrush currents)	●
Phase sequence detection	●
Data transfer to PC via HTAgorà software	●
Simultaneously recordable electrical parameters with a programmable integration period	● 3180
USB, Ethernet, and Wi-Fi connectivity	●
Memory card	●

GENERAL SPECIFICATIONS

Dimensions (L x W x H)	235 x 165 x 75 mm / 9 1/4 x 6 1/2 x 3 in
Weight (including batteries)	1.2 kg / 2 lb 10 oz
Operating temperature	from -10°C to 50°C / from 14°F to 122°F
Operating humidity	<80% RH
Protection rating	IP40
Battery power supply	6x 1.5V AA LR06 alkaline batteries 6x 1.2V AA LR06 NiMH rechargeable batteries
Mains power supply	External charger adapter 100-415VAC 50/60Hz / 15VDC

ACCESSORIES

STANDARD ACCESSORIES

HTFLEX335	Flexible clamp 6000A AC with 5-pin connector, max cable diameter 174mm, 4 pcs
YMETK0042HT0	Label kit for input color customization (according to national standards)
KIT802	Set of 5 black banana-banana cables and 5 black alligator clips, plus set of colored rings (9 colors)
A0080	External power supply with plug cable
PT400	Stylus (included in the instrument's right flip)
C2010	USB-A / USB-C connection cable
CF832	32GB memory card
YAMUM0088HT0	Quick start guide
YABAT0003000	Rechargeable AA NiMH batteries, 1.2V, 6 pcs
VA500	Hard carrying case
Test Report	

OPTIONAL ACCESSORIES

HTFLEX315	Flexible clamp 6000A AC with 5-pin connector, max cable diameter 80mm
HTFLEX355	Flexible clamp 10000A AC with 5-pin connector, max cable diameter 270mm
HT4005N	Standard clamp with 5-100A AC range with 3-pin connector
HT96U	Standard clamp with 1/100/1000A AC range with 3-pin connector
HT97U	Standard clamp with 10/100/1000A AC range with 3-pin connector
HP30C2	Standard clamp with 200/2000A AC range with 3-pin connector
HP30C3	Standard clamp with 3000A AC range with 3-pin connector
607-IECN	Magnetic terminal connector
ACON3F5M	3-pin / 5-pin adapter (to use standard clamps)
SP-0500	Set of straps and hooks for shoulder use

HT ITALIA S.R.L.

Via della Boaria, 40 - 48018 Faenza (RA) - Italy

T +39 0546 621002 | **F** +39 0546 621144

M export@ht-instruments.com | **ht-instruments.com**

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.



Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

