

# DET4TC2 and DET4TCR2

## Digital Ground Testers



- IP54 rated
- 2, 3 and 4 point testing
- Attached Rod Technique (ART)
- Stakeless measurements
- User selectable test frequency
- Dry cell or rechargeable versions
- User selectable output voltage
- Simple one button operation
- Robust carry case
- Backlit display
- Delivered with calibration certificate

### DESCRIPTION

Megger's DET4 family of ground testing instruments offers a comprehensive solution to your ground stake and soil resistivity testing needs. The standard instrument comes with test leads, stakes, terminal adaptors for bare wire, batteries and calibration certificate are delivered in a tough carry case which has space to accommodate all the instrument accessories - everything you need to start testing in one kit.

The DET4TC2 and DET4TCR2 are designed for extended temperature range use with an IP54 rated enclosure making them genuinely outdoor instruments. The instrument provides all the functions required for ground system testing: variable frequency 2 pole, 3 pole, 4 pole, Attached Rod Technique (ART), stakeless, leakage current and ground noise voltage measurement.

The instrument is easy to use with a large rotary selector switch and one-press test button, both of which permit operation with gloved hands. Unlike some instruments, the design negates the need for a shorting link when making two pole measurements. There are no hidden functions with the instrument: clearly labelled auxiliary controls are used to select the test frequency (94 Hz, 105 Hz, 111 Hz and 128 Hz), output voltage (50 V or 25 V where local standards apply) and to switch the backlight on or off.

The optional MCC CLAMP augments the traditional fall-of-potential measurement method with ART (Attached Rod Technique) which allows electrode testing without disconnection and also leakage current measurements down to 1 mA. A second optional clamp, the MVC CLAMP, enables true stakeless measurements to be made in situations where driving stakes is not practical.

The clear, easy-to-read display provides excellent contrast and viewing angle making the instrument ideally suited to outdoor use. The display is backlit, extending the operational environment of the instrument to cable cellars and other dark locations.

The instrument offers a wide measurement range of 0.01  $\Omega$  a to 200 k $\Omega$ , ground noise voltage measurement from 1 V to 100 V and ground current from 1 mA to 20 A. Accurate results can be obtained in electrically noisy environments since the instrument is capable of rejecting noise voltages of 40 V peak to peak and the user can select different test frequencies to minimise the effect of interference.

The DET4TC2 digital ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TCR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is display using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

**SPECIFICATIONS****Ingress protection**

IP54

**C stake, P stake and Noise check**

Automatic

**Noise rejection**

40 V pk to pk

**2-wire, 3-wire, 4-wire test**

Yes, no shorting links required

**No disconnect testing (ART)**

Yes, with MCC CLAMP

**Stakeless measurement**

Yes, with MCC CLAMP and MVC CLAMP

**Instrument output**Voltage:  $\pm 25$  V or  $\pm 50$  V at 94 Hz, 105 Hz, 111 Hz and 128 Hz

Current: 4.5 mA or 0.45 mA or 0.045 mA

**Ground current range with clamp**

0.5 mA to 19.9 A

**Ground current accuracy**5%  $\pm 3$  digits**Ground voltage range**

0 to 100 V ac

**Ground voltage accuracy**2%  $\pm 2$  V**Resistance ranges**2, 3, 4 pole: 0.01  $\Omega$  to 200 k $\Omega$ ART: 0.01  $\Omega$  to 200 k $\Omega$ Stakeless: 0.01  $\Omega$  to 200  $\Omega$ **Resistance accuracy**2P measurements: 2%  $\pm 3$  digits3P measurements: 2%  $\pm 3$  digits4P measurements: 2%  $\pm 3$  digitsART measurements: 5%  $\pm 3$  digitsStakeless measurements: 7%  $\pm 3$  digits**Maximum probe resistance**Rp limit: 200 k $\Omega$  (50 V output voltage)Rc limit: 200 k $\Omega$  (50 V output voltage)Limits reduced to 100 k $\Omega$  for 25 V output voltageLimits reduced to 5 k $\Omega$  for 0.01  $\Omega$  resolution**Display**

3½ digit high contrast liquid crystal, backlit

**Battery type**

DET4TC2: 8 off AA (LR6) cells

DET4TCR2: 8 off AA (LR6) NiMH rechargeable cells

**Operating temperature range**

-15 °C to +55 °C / 5 °F to 131 °F

**Storage temperature range**

-40 °C to +70 °C / -40 °F to 158 °F

**Safety**

Complies with the requirements of IEC61010-1 100V CAT IV between terminal pairs.\*

**EMC**

In accordance with IEC61326-1

**Standards Compliance**

Complies with the requirements of KEMA K85B

Complies with the following parts of EN61557, "Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures".

Part 1 - General requirements

Part 5 - Resistance to earth

**Dimensions**

203 mm x 148 mm x 78 mm (8 in x 5.8 in x 3 in)

**Weight**

1kg (2.2lb)

\*The CAT IV 100 V rating is dependant on the use of a leadset of at least this rating, for example the optional two wire leadset part number 1001-858.

**ORDERING INFORMATION**

Item	Order Code.	Item	Order Code.
DET4TC2	1000-345	<b>Accessories</b>	
DET4TCR2 (rechargeable)	1000-346	Replacement hard carry case	5410-429
<b>Included Accessories</b>		Replacement calibration check PCB (two-clamp measurements)	1000-434
Hard carry case		Replacement ground test stakes (x2) for included kit (200 mm, 8 mm dia)	6220-804
Stake and wire kit (15 m, 10 m, 10 m, 3 m)		Replacement ground test leads (x4) for included kit (15 m, 10 m, 10 m, 3 m)	6220-806
Right angle terminal adaptors (to connect bare wires to terminals)		Replacement cable reel (50 m, red + spike)	1010-844
External AC/DC charger (DET4TCR2 only)		Replacement cable reel (30 m, black + spike)	1010-848
<b>Kitted options for ART and Stakeless testing</b>		Replacement cable reel (50 m, yellow + spike)	1010-842
DET4TC2 + clamps	1000-365	Replacement cable reel (30 m, green + spike)	1010-849
DET4TCR2 + clamps (rechargeable)	1000-366	Replacement external AC/DC adaptor (DET4TCR2 only)	6280-370
<b>" + clamps " included Accessories</b>		MCC CLAMP	1010-516
Hard carry case		MVC CLAMP	1010-518
Stake and wire kit (15 m, 10 m, 10 m, 3 m)		Calibration check box (25 Ohm)	1000-435
MCC CLAMP (for ART testing)		Right angle terminal adaptor set	1012-511
MVC CLAMP (adds stakeless testing)		Black crocodile clip (1)	6220-850
Field calibration check for instrument and CLAMPS		"Getting down to earth"	
Right angle terminal adaptors (to connect bare wires to terminals)		Megger guide to earth ground testing	21500-072
External AC/DC charger (DET4TCR2 only)		Leadset	1001-858
<b>Professional kitted options for ART and Stakeless testing</b>			
DET4TC2 + ETK50C	1012-521		
DET4TCR2 + ETK50C	1012-523		
<b>" + kit " included Accessories</b>			
Hard carry case			
Stake and wire kit (15 m, 10 m, 10 m, 3 m)			
MCC CLAMP (for ART testing)			
MVC CLAMP (adds stakeless testing)			
Field calibration check for instrument and CLAMPS			
External AC/DC charger (DET4TCR2 only)			
Separate ETK50C 2x 50m, 2x 30m complete with spikes and tape measure in weather proof holdall			

# Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



## KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

## Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

## EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

