

## DET4TD2 and DET4TR2 Digital Ground Testers



- IP54 rated
- 2, 3 and 4 point testing
- Selectable 25 V or 50 V output
- Dry cell or rechargeable versions
- Simple one button operation
- Robust carry case

### DESCRIPTION

Megger's DET4 family of ground testing instruments offers a unique solution to your ground rod and soil resistivity testing needs. The standard instrument comes with, test leads, stakes, terminal adaptors for bare wire, batteries and calibration certificate delivered in a tough polypropylene carry case - everything you need to start testing in one kit.

The ground testers are rated to IP54 making it truly an outdoor instrument. The ground tester has been designed to be easy to use, a large selector switch makes selection of 2 pole, 3 pole or 4 pole test easy with gloved hands - and the design makes the fitting of shorting links to perform 2 pole tests a thing of the past. A large, clear, easy to read LCD display and thumb sized test button again makes the instrument particularly suited to the outdoor conditions of ground testing.

In addition to this ease of use the ground tester also automatically checks the connection and condition of the P spike and the C spike, indicating the status on the display. The instrument also includes a voltmeter to allow you to measure the ground voltage. The ground tester can measure resistance from 0.01  $\Omega$  through to 20 k $\Omega$  and earth voltages up to 100 V. To allow testing in noisy environments the instrument is capable of rejecting noise of up to 40 V peak to peak.

The DET4TD2 digital ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is displayed using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

## DET4TD2 and DET4TR2 Digital Ground Testers

### SPECIFICATIONS

<b>IP rating</b>	IP54
<b>C stake, P stake and noise check</b>	Automatic
<b>Noise rejection</b>	40 V peak to peak
<b>2 wire, 3 wire, 4 wire test</b>	Yes, no shorting links required
<b>Instrument output</b>	
Voltage:	±25 V or ± 50 V at 94 Hz, 105 Hz, 111 Hz and 128 Hz
Current:	4.5 mA or 0.45 mA or 0.045 mA
<b>Resistance range</b>	2, 3, 4 pole: 0.01 Ω to 200 kΩ
<b>Maximum probe resistance</b>	
Rp limit:	100 kΩ (50 V output voltage)
Rc limit:	100 kΩ (50 V output voltage)
Limits reduced to 50 kΩ for 25 V output voltage	
Limits reduced to 5 kΩ for 0.01 Ω resolution	
<b>Earth / ground voltage range</b>	
0 to 100 V ac	
<b>Earth / ground voltage accuracy</b>	
2% ±2 V	
<b>Display</b>	3½ high contrast liquid crystal, backlit
<b>Power supply</b>	DET4T2 8 off AA (LR6) cells DET4TR2 8 off AA (LR6) NiMH rechargeable cells
<b>Battery charger:</b>	100-240 VAC (50/60 Hz)
<b>Operating temperature range and humidity</b>	
-15 to +55 °C (5 °F to 131 °F)	
<b>Storage temperature range and humidity</b>	
-40 to +70 °C (-40 °F to 158 °F)	

### Safety

Complies with the requirements of IEC61010-1 100 V CAT IV between terminal pairs.

The CAT IV 100 V rating is dependant on the use of a leadset of at least this rating, for example the optional two wire leadset part number 1001-858.

### EMC

In accordance with IEC61326-1

### Compliance

Complies with the requirements of KEMA K85B.

Complies with the following parts of EN61557, "Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures".

Part 1 - General requirements

Part 5 - Resistance to earth

<b>Dimensions</b>	203 mm x 148 mm x 78 mm
<b>Weight</b>	1 kg

## DET4TD2 and DET4TR2 Digital Ground Testers

### ORDERING INFORMATION

Description	Part number	Description	Part number
<b>Product</b>		<b>Optional accessories</b>	
DET4TD2	DET4TD2	Replacement hard carry case	5410-429
DET4TR2 (rechargeable)	1000-324	2 replacement earth test spikes (200 mm, 8 mm dia.)	6220-804
<b>Included accessories</b>		Replacement ground test leads (x4) for included kit (15 m, 10 m, 10 m, 3 m)	6220-806
Hard carry case		Battery charger (DET4TCR2 only)	6280-370
Stake and wire kit (15 m, 10 m, 3 m)		Calibration check box (25 Ohm)	1000-435
Right angle terminal adaptors (to connect bare wires to terminals)		Right angled terminal adaptor set	1012-511
Battery charger (DET4TCR2 only)		Black crocodile clip (1)	6220-850
		ETK50 2 x 50 m, 2 x 30 m, complete with spikes and tape measure, in a weather proof holdall	1010-177
		Vehicle 12 V socket charger (rechargeable versions only)	6280-375
		'Getting down to earth' A Megger guide to earth testing	21500-072
		Leadset	1001-858

#### SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T +44 (0) 1304 502101  
E UKsales@megger.com

#### DET4TD2\_DET4TR2\_DS\_en\_V13

www.megger.com  
ISO 9001

The word 'Megger' is a registered trademark

# Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



## KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

## Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

## EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

