

EVCA210/EVCA210-UK Electric vehicle charge-point adaptor



- Push Button for PE Pre-Test
- Push button for CP Error "E" simulation
- Push button for PE Error (Earth Fault) simulation
- Rotary switch providing PP State simulation
- Rotary Switch providing CP State simulation
- Type 1 to Type 2 Adaptor available (Supplied as standard with the EVCA210-UK)
- Carrying Case
- CAT II 300V Rating
- Comply with Low Voltage Directive LVD 2014/35

DESCRIPTION

The Megger EVCA210/EVCA210-UK are compact, simple to use adapters designed to perform all the functions required by the electrical contractor to fully test Mode 3 AC Electric Vehicle Charge-points. Specially designed to comply with UK, European and other International wiring regulations and standards, the EVCA210/EVCA210-UK may be used on all single and three phase electric vehicle charge points, with appropriate connectors. They are designed to test the function and safety of a charging point. The adapters allow you to conduct tests using appropriate single or multifunction test instruments on EV charging points in accordance with IEC/EN 61851-1 and IEC/HD 60364-7-722. Charging points should be tested as part of the initial installation and repeated periodically.

The Megger EVCA210/EVCA210-UK test adaptors are designed to simulate the connection of an electrical vehicle to the charging point under test. Connection of the adapter enables the operator to trigger the charging process by selecting the appropriate Proximity Pilot (PP) and Control Pilot (CP) states.

Test instruments can be connected using either the front mounted mains socket or the 4mm connection ports L1, L2, L3, N, PE. 2 additional CP signal terminals give the operator the ability to measure the CP signal using an oscilloscope.

In addition, the adapters have a manual PE Pre-Test feature that allows the user to test for dangerous voltages present on the PE, prior to any other testing of the charge point. If this test fails, testing must cease as potentially dangerous voltages may be present on the PE and faults must be investigated and rectified before continuing. The adapters also integrate two further manual tests: CP Error – simulates an error on the control pilot circuit; and a PE Error – where a disconnection of the PE circuit is produced. Both test ensure correct disconnection of the output of the charge point. Before carrying out testing with this adaptor, it is recommended that the user familiarize themselves with the relevant standards:

IEC 61851-1:2017, Electric vehicle conductive charging system - Part 1: General requirements

EVCA210/EVCA210-UK

Electric vehicle charge-point adaptor

IEC 60364-7-722:2018 Low-voltage electrical installations
 - Part 7-722: Requirements for special installations
 or locations - Supplies for electric vehicles and any
 documentation relating to the charging station itself.

All Megger EVCA210 variants are supplied with a fixed Type
 2 connector plug. The EVCA210-UK is also supplied with
 a Type 2 to Type 1 adaptor plug as standard - optional for
 other variants.

	EVCA210	EVCA210-UK
Input voltage 250 V (single phase system) / 430 V (three phase system),	■	■
Push Button for PE Pre-Test	■	■
Rotary switch providing PP State simulation	■	■
Rotary Switch providing CP State simulation	■	■
Push button for CP Error "E" simulation	■	■
Push button for PE Error (Earth Fault) simulation	■	■
Measurements on live conductors (L1, L2, L3 and N) and on PE conductor	■	■
Mains Socket: EVCA210-UK - 13A UK socket EVCA210 - Schuko socket (CEE 7/3)	■	■
CP signal test, two 4 mm ports for connection to an oscilloscope	■	■
CAT II 300 V	■	■
Fixed Type 2 Plug for charging points with panel mounted socket outlet or fixed cable with vehicle connector.	■	■
Type 1 to Type 2 adaptor for charging points with fixed cable and vehicle connector – Supplied with EVCA210-UK as standard		■
Soft Carry Case	■	■

EVCA210/EVCA210-UK

Electric vehicle charge-point adaptor

SPECIFICATIONS

Input voltage	Up to 250 V (single phase system) / up to 430 V (three phase system)	Altitude above sea level.	2000 m max.
Input Frequency	50/60 Hz,	Dimensions (W × H × L)	225 mm x 145 mm x 62 mm (without connection cable and test cable)
PE Pre-Test	Yes – Push button	Weight	Approx: 780g
CP Error “E” simulation	Push button	CE directive	Low Voltage Directive LVD 2014/35/EU
PP Simulation	NC, 13 A, 20 A, 32 A, 63 A	Safety	IEC/EN 61010-1:2010 IEC/EN 61010-2-030:2010
CP States	A, B, C, D	Working temperature range	0 to +40 °C
CP Error “E”	Yes	Storage temperature range	-10 to +50 °C
PE Error (Earth fault)	Yes	Reference humidity range	10 to 60% relative humidity w/o condensation
Measuring Ports L1, L2, L3, N and PE	Max. 250/430 V, CAT II 300 V, max. 10 A	Working humidity range	10 to 85% relative humidity w/o condensation
Mains socket	Max. 250 V, CAT II 300 V, max. 10 A, Note: Do not load mains socket simultaneously with measuring ports!		
CP Signal Test Ports	Approx. +/-12 V, CAT 0 (under normal condition)		
Measurement category	CAT II 300 V		

ORDERING INFORMATION

Description	Part number	Description	Part number
EVCA210-UK (UK Mains Socket)	1012-732	EVCA210 (Schuko Mains Socket)	1013-317
Included accessories		Included accessories	
Type 1 to Type 2 Charging Plug Adaptor		EVCA210	
Fixed Type 2 Charging Plug		Fixed Type 2 Charging Plug	
EVCA210 Carry Case		Soft Carry Case	
Instruction Manual		Instruction Manual	
		Optional accessories for EVCA210 & EVCA210-UK	
		EVCA210 Soft Carry Case	1013-318
		Type 1 to Type 2 Plug Adaptor	1014-901
		EVCA210-CH EV adaptor	1013-832
		EVCA210-AU EV adaptor	1015-141

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

EVCA_DS_en_V05

www.megger.com
ISO 9001

The word 'Megger' is a registered trademark

Megger ^R

Les services d'EURO-INDEX

EURO-INDEX fournit des services pour tous les instruments de sa gamme de fournitures et offre des services, de la connaissance et du personnel hautement qualifié pour l'entretien (préventif), la réparation et le calibrage de vos instruments de mesure.

Centre de Service Agréé.....

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées.

Autrement dit, vos instruments sont traités par du personnel formé et compétent, qui dispose des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument ainsi que la certification (ATEX, EN50379, etc.) restent valables.

Laboratoire de maintenance et de calibrage

EURO-INDEX dispose d'un laboratoire de maintenance et de calibrage particulièrement moderne, titulaire d'une accréditation conforme à la norme NEN-EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105.



MQS®

MQS est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure. La prise en charge de multiples aspects vise à vous libérer de tout souci lors de l'utilisation de vos instruments de mesure. Les coûts sont modiques et prévisibles.

Accès numérique à vos certificats de calibrage avec Mon MQS

Mon MQS est un portail Web qui vous donne accès partout et à tout moment à vos certificats de calibrage et aux documents apparentés.

Location d'instruments de mesure

- Vaste assortiment
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires et leurs certificats de calibrage traçables

EURO-INDEX Academy

- Formations sur les produits (individuelles et collectives)
- Séminaires
- Vidéos de démonstration et d'instruction

Visionnez la vidéo sur notre chaîne YouTube et découvrez tout ce qu'il vous faut savoir sur MQS



Guichet des services



Calibrage de l'analyse de gaz de combustion



Séminaires et ateliers



Calibrage de la thermographie

Sous réserve de modifications EURO-INDEX® FR 18001

Le nom et la marque Bluetooth® sont la propriété de Bluetooth SIG Inc. L'utilisation de ce nom par EURO-INDEX s'effectue sous licence.



BELGIQUE
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

PAYS-BAS
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



Portée accréditée
voir www.rva.nl