

## EVX100

### EV charger interface for the MFT-X1



- Fully integrated to the current MFT-X1
- Simple operation
- Integrated with MFT-X1 control interface
- Automated EV charger resetting
- Full EV control by the MFT-X1
- CP code reporting
- IP54 compliance
- CAT II 250 V rating
- Carry case included

#### DESCRIPTION

The EVX100 is designed as a fully integrated accessory to the MFT-X1 offering an automated test interface for testing single and three-phase Mode 3 AC electric vehicle charging stations (Mode 3 EVSE chargers).

The EVX100 in combination with the MFT-X1 offers the ideal test solution for installation verification and servicing of EV chargers, removing the need for the traditional remotely located manual adaptor/control box.

When the EVX is connected to the MFT-X1 the instrument recognises the EVX100 and the MFT automatically offers the operator the necessary EV charger testing options with no need to touch the EVX interface.

The EVX100 offers a range of EV charger testing options, all controlled through the MFT-X1 test interface, including single and 3 phase. There is no need for manual controls or additional test leads.

PP and CP states are controlled automatically, simplifying the operation of the testing procedures. The MFT-X1 can identify all four operational CP states, A, B, C and D as well as the intermediate state A1, A2, B1, B2 etc. This provides enhanced operational awareness and diagnostic feedback during error conditions.

In addition, the EVX will also identify PE issues through the MFT-X1 rather than the manual adaptor touch buttons. This is operated via the dual (ambidextrous) test buttons on the MFT and will inhibit or just warn the user of any issues depend on the MFT configuration.

The PE warning function now works via the MFT-X1 when touching the test buttons.

The EVX100 is supplied with the Type 2 charging plug. Testing of IEC61851 and IEC62955 protective devices is automated through the EVX.

When an RCD trips during an RCD or RDC test the EVX automatically generates an EV charger reset. As soon as power is restored to the charger the EVX resets the charger, removing the need for user to select C-B-A-B-C on the CP knob of a manual adaptor.

The EVX will operate with all existing MFT-X1 instruments with the latest free firmware update from the Megger website.

The EVX100 is powered by a lithium-Ion battery with USB type C charging port.

Achieving IP54, the adaptor meets the same IP standard as its MFT host and enables its use in inclement weather.

Leveraging all the test capabilities of the MFT-X1 the combination of EVX100 and MFT-X1 offers an exceptionally simple and flexible solution to electricians working on both the incomm and load side of the EV charging station.

# EVX100

## EV charger interface for the MFT-X1

### FEATURES

	<b>EVX100 interface</b>	<b>Optional accessory</b>
EVX100 interface	✓	
Test lead	✓	
Type 2 plug	✓	
Type 1 plug		✓
CAT II 250V compliance	✓	
IP rating IP54	✓	
Rechargeable Li-ION battery	✓	
Type C charging lead	✓	
Carry case	✓	
Quick start guide	✓	
Full user guide	✓	Available online
Safety warnings	✓	

### SPECIFICATIONS

<b>Power supply:</b>	
<b>Internal battery:</b>	Li-ion 3180 mAH
<b>Recharging:</b>	Type C USB (required supply is 5 V, 1 A maximum)
<b>Charging status:</b>	LED
<b>Input voltage</b>	
<b>230 V AC nominal</b>	max 253 V AC
<b>400 V AC nominal</b>	max 440 V AC
<b>Input frequency:</b>	50/60 Hz
<b>CP state verification:</b>	A1, A2, B1, B2, C1, C2, E, F
<b>For measurement specification refer to the MFT-X1 user guide.</b> See <a href="http://megger.com/mft-x1">megger.com/mft-x1</a>	
<b>Connection options:</b>	Fixed type 2: IEC 62196-1
<b>Safety:</b>	IEC61010-1:2010 61010-031:2015, CAT II 250 V
<b>Temperature range:</b>	
<b>Working range:</b>	-10 °C to +55 °C
<b>Storage range:</b>	-25 °C to +70 °C
<b>Humidity range:</b>	90% R.H at +40 °C max
<b>Ingress protection:</b>	IEC 660529: IP 54: Equipment is protected against ingress of dust and water splashes and is suitable for indoor and outdoor use.
<b>Vibration:</b>	MIL-PRF-28800F: Class 2
<b>Maximum operating altitude:</b>	2000 m
<b>Pollution degree:</b>	2
<b>Mechanical</b>	
<b>EVX case dimensions:</b>	133.5 x 115 x 56 mm (5.2 x 4.5 x 2.2 inches) excl. cable.
<b>Unpackaged weight:</b>	976 g
<b>Packaged dimensions:</b>	350 x 280 x 75 mm (13.8 x 11.02 x 2.96 inches)
<b>Packaged weight:</b>	1580 g
<b>Cable length:</b>	2 m

### ORDERING INFORMATION

Description	Part number
EVX100	1016-183
<b>Included accessories</b>	
Carry case	2017-285
User guide	2017-287
<b>Optional accessories</b>	
EVX100 carry case	2017-285
Type 1 to type 2 adaptor	1014-901

### SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T. +44 (0) 1304 502101  
E. UKsales@megger.com

### EVX100-DS-EN-V03

[www.megger.com](http://www.megger.com)  
ISO 9001  
The word 'Megger' is a registered trademark

# Services d'EURO-INDEX

**EURO-INDEX est un fabricant, importateur et distributeur de diverses marques A dans le domaine des instruments de test et de mesure. Nous fournissons également une large gamme de services pour optimiser l'utilisation de ces instruments dans vos activités. Ces services comprennent naturellement l'entretien, la réparation et l'étalonnage des instruments, mais nous proposons aussi une assistance sous forme de formation via notre EURO-INDEX Academy et la location d'instruments.**

## Centre de Service Agréé

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées. Cela signifie que vos instruments sont pris en charge par des techniciens formés par le fabricant et disposant des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument, ainsi que les certifications (ATEX, EN50379, etc.) restent intactes.



## Laboratoire de maintenance et de calibrage

Le laboratoire des Pays-Bas est accrédité RvA selon la norme EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105. Les certificats de calibrage RvA sont acceptés à l'international et équivalents à ceux de BELAC.



## Service Mobile

Outre les laboratoires d'étalonnage fixes de Zaventem et de Capelle aan den IJssel, nous disposons également d'un laboratoire itinérant appelé "Service mobile". Nos services puissent venir vers vous, en offrant une qualité équivalente.

## MQS®

MQS® est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure à un coût fixe et faible. Via un portail Web gratuit ([monmqs.be](http://monmqs.be)), vous avez toujours accès à vos certificats de calibrage.

## Location d'instruments de mesure

- Vaste assortiment
- Précision démontrable par le certificat d'étalonnage actuel
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires

## EURO-INDEX Academy

- Formations et séminars
- Vidéos de démonstration et d'instruction
- Notes d'application



Comptoir de service



Entretien, réparation et calibrage



Formations et séminars



Service Mobile

Sous réserve de modifications EURO-INDEX® FR 23001



BELGIQUE

Chaussée de Louvain 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
[sales@euro-index.be](mailto:sales@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)

PAYS-BAS

Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)

