

PAT400 Series Portable appliance testers



- 10,000 memory storage with USB download
- Large 5.7" $\frac{1}{4}$ VGA backlit full colour screen for clear results
- 200 mA; 10 A and 25 A Bond Test with high duty cycle for repetitive testing (PAT410 - 200 mA only)
- Selectable PASS/FAIL limits provide instant indication of a faulty asset
- Optional barcode scanner and printer available to save time typing asset IDs
- 230 V and 110 V operation for industrial, commercial and residential applications

DESCRIPTION

The PAT400 series from Megger is a new generation of downloading portable appliance testers, fully testing portable electrical equipment to the latest edition of the Code of Practice for the In-Service Inspection and Testing of Electrical Equipment. There are 3 products in the range; the PAT410 providing a low-profile 230 V only solution without the added weight required of 110 V operation, plus a database capacity for up to 10,000 test results. The PAT420 provides the same extensive memory and downloading capability, and has the added features of 110 V operation, and also 10 A and 25 A earth bond testing. The PAT450, the top of the range, has all of these features and includes 1.5 kV and 3 kV flash testing, ideal for tool hire outlets and service workshops where flash testing is routine. All products in the range have a high duty-cycle, with the design tailored to fast testing, easy operation, and all-day use. The PAT400s feature a unique fast-re-start, so that when moving the tester from one room to another, it re-starts instantly from the same menu where it was unplugged. This is a significant timesaver, so allowing more tests per day.

USB communication provides convenient download to a standard USB memory stick., and an on-board 10,000 record memory provides interruption-free testing for improved efficiency, with a large QWERTY keypad for fast data entry. Data is directly compatible with Megger PowerSuite® software for professional certification, and all products have the option of a barcode scanner and a thermal transfer barcode label printer operating directly from the USB port. Thermal transfer labels are highly resistant, stable and easily available. The PAT420 and PAT450 have dual 230 V and 110 V operation

for complete industrial, commercial and residential applications.

5 soft-keys give direct access to frequently used functions, accelerating navigation through menus and therefore increasing productivity, where time is money. Both standard and customer configurable test groups are available for fast, flexible asset testing.

Tests available in the range include 250 V and 500 V insulation tests, 200 mA, 10 A and 25 A earth bond tests, differential, touch and alternative (substitute) leakage tests, operational VA tests, RCD trip-tests for portable RCDs, anti-surge and RCD protected extension leads and power cords. RCD testing is now a requirement of the UK Code of Practice.

Accessories supplied with all models include a combined earth-bond and insulation test lead, an adaptor for testing 230 V extension leads, a laptop power supply adaptor, and a carry-case for convenient product and lead storage. All instruments also include Download Manager software, to enable data to be converted into a CSV format which can be read directly on a PC using Microsoft® Excel.

Megger PowerSuite software can be purchased to compliment any PAT400, providing full databased asset management and professional electronic certificate generation, providing options for multiple clients and locations.

PAT400 Series

Portable appliance testers

APPLICATION

There is a legal requirement for any landlord, employer or owner of a place of work or public place, to ensure that all electrical equipment accessible by tenants, employees or the public is maintained in a safe condition, and an acceptable method of ensuring this is by routine electrical testing. This can be performed by electrical contractors, specialist PAT testing organisations, maintenance departments, or facilities management companies.

The PAT400 range is suitable for performing portable appliance testing in locations such as hotels, public houses, schools, colleges, nurseries, shops, offices, theatres, banks, restaurants, cafés, sports and leisure facilities, cinemas, factories and hair salons etc. where high volume testing requires that accurate records may be difficult to maintain, or aided by, on-board memory and download to management software. The PAT450 is particularly suitable for use in tool-hire shops where equipment is routinely tested prior to hire, or service workshops where deep disassembly is routine, and will perform a flash test in addition to standard PAT tests.

	PAT410	PAT420	PAT450
SUPPLY			
230 V	■	■	■
110 V		■	■
Supply measurement	■	■	■
EARTH BOND/CONTINUITY			
200 mA	■	■	■
10 A		■	■
25 A	■	■	■
Bond lead null	■	■	■
INSULATION TEST			
250 V	■	■	■
500 V	■	■	■
ALTERNATIVE LEAKAGE TESTS			
Substitute	■	■	■
Differential	■	■	■
Touch current	■	■	■
OPERATION TEST			
VA Measurement	■	■	■
EXTENSION LEAD TEST			
Earth bond	■	■	■
Insulation	■	■	■
Polarity	■	■	■
Portable RCD test (230 V)	■	■	■
FLASH TEST			
1.5 kV and 3 kV			■
OTHER FEATURES			
Low-profile light weight	■		
Auto test routine	■	■	■
Manual testing	■	■	■
Fuse check	■	■	■
Colour display	■	■	■
110 V test connection		■	■
Configurable tests times	■	■	■
Selectable pass limits	■	■	■
Lead storage pouch	■	■	■
10,000 record on-board storage	■	■	■
Download to USB memory stick	■	■	■
PowerSuite compatible	■	■	■

PAT400 Series Portable appliance testers

SPECIFICATIONS

Electrical supply range

PAT410, PAT420, PAT450 230V $\pm 10\%$ $\pm 1V$ @ 50Hz
 $\pm 10\%$ $\pm 0.1Hz$

PAT420, PAT450 110V $\pm 10\%$ $\pm 1V$ @ 50Hz
 $\pm 10\%$ $\pm 0.1Hz$

Instrument accuracy cannot be guaranteed when operated on supply frequencies other than those specified above

Bond test: (10 A and 25 A) (not PAT410)

Open circuit voltage: 9 V a.c. $\pm 10\%$ $\pm 0.1 V$ (Supply: 230 V 50 Hz)

Earth bond resistance accuracy: $\pm 5\%$ ± 3 digits (0 to 0.49 Ω)
 $\pm 5\%$ ± 5 digits (0.5 to 1.99 Ω)

Earth bond resistance resolution: 10 m Ω (0 to 1.99 Ω)

Display range: 0 to 1.99 Ω

Continuity (200mA)

Continuity test voltage: 4.0 V DC -0% +10%

Continuity resistance accuracy: $\pm 5\%$ ± 3 digits (0 to 0.49 Ω)
 $\pm 5\%$ ± 5 digits (0.5 to 19.99 Ω)

Continuity resistance resolution: 10 m Ω (1 to 19.99 Ω)

Display range: 0 to 19.99 Ω

Insulation test (250 V and 500 V)

Insulation resistance accuracy (230 V): $\pm 2\%$ ± 5 digits (0 to 19.99 M Ω)
 $\pm 5\%$ ± 10 digits (20 to 99.99 M Ω)

M Ω)

Insulation resistance resolution: 0.01 M Ω

Display range: 0 to 99.99 M Ω

SUBSTITUTE LEAKAGE CURRENT

Test voltage and frequency: 40 V a.c. $\pm 10\%$ nominal mains frequency

Leakage current accuracy: $\pm 5\%$ ± 5 digits

Leakage current resolution: 0.01 mA

Display range: 0 to 19.99 mA

LEAKAGE CURRENT

Test voltage and frequency: Nominal mains supply

Differential leakage current accuracy: $\pm 5\%$ ± 5 digits

Differential leakage current resolution: 0.01 mA

Display range: 0 to 19.99 mA

TOUCH CURRENT TEST

Test voltage and frequency: Nominal mains supply

Touch current accuracy: $\pm 5\%$ ± 5 digits

Touch current resolution: 0.01 mA

Display range: 0.00 to 10 mA

OPERATIONAL TEST

Test voltage and frequency: Nominal mains supply

VA accuracy: $\pm 5\%$ ± 10 digits (0 - 99 VA)
 $\pm 5\%$ ± 50 digits (100 VA - 999 VA)
 $\pm 5\%$ ± 100 digits (1000 VA - 3700 VA)

Resolution: 1 VA (0 to 3700 VA)

Display range: 0 to 3.99 VA
Ext Lead Test

Tests performed: Bond, insulation and polarity

Polarity test voltage: 12 V DC

Polarity checks: Lead OK
Live neutral S/C
Live neutral reverse
Live/neutral O/C
Ext Lead Test

Tests performed: Bond, insulation and polarity

Polarity test voltage: 12 V DC

Polarity checks: Lead OK
Live neutral S/C
Live neutral reverse
Live/neutral O/C
Flash test

Flash test voltage: 1500 V AC nominal for Class 1
3000 V AC nominal for Class 2

Flash test current: <3.5 mA short circuit @ 253 V primary supply voltage

Flash test breakdown current accuracy: $\pm 5\%$ ± 5 digits

Flash test breakdown current resolution: 0.01 mA

Display range: 0.00 to 3.0 mA

RCD TESTS

Test voltage and frequency: 230 V 50 Hz

Test current accuracy: -8% to -2% (1/2 x I)
+2% to +8% (1 x I, 5 x I)

Trip time accuracy: $\pm 1\%$ ± 5 digits

Trip time resolution: 0.1 ms

Display range: 0 to 1999 ms (1/2 x I)
0 to 300 ms (1 x I)
0 to 40 ms (5 x I)

PAT400 Series

Portable appliance testers

FUSE TEST

Test voltage: 3.3 V

Warning: Audible beep if fuse is OK

Operating temperature

range and humidity: -10 to +50 °C
90% RH @ -10 to +30 °C
75% RH @ +30 to +50 °C

Storage temperature

range and humidity: -20 to +60 °C
90% RH @ -10 to +30 °C
75% RH @ +30 to +50 °C

Maximum altitude: 2000 m

IP rating: IP40

Dimensions: PAT410 145 (H) x 255 (B) x 320 (L)
PAT420 180 (H) x 255 (B) x 320 (L)
PAT450 180 (H) x 255 (B) x 320 (L)

Dimensions (instrument

and packaging): 210 mm (H) x 280 mm (W) x 390 mm (L)

Weight: PAT410 (with packaging) 2,7 kg (3,2 kg)
PAT420 (with packaging) 4.4 kg (4.9 kg)
PAT450 (with packaging) 5,0 kg (5,5 kg)

Over-voltage

safety category: IEC 61010-1: CAT II 300 V

EMC: IEC 61326-1: 2006
IEC 61326-2-2: 2005

ORDERING INFORMATION

Description	Order Code	Description	Order Code
PAT410-UK	1000-745	<i>Optional accessories</i>	
PAT420-UK	1000-752	UKAS certificate	1001-285
PAT450-UK	1000-755	110 V Extension lead adaptor	6220-639
<i>Included accessories</i>		110 V mains lead adaptor	1000-766
Printed quick start guide		415 V adaptor lead (4-pin) to BS1363 (16 A)	1000-767
Full user guide on CD		415 V adaptor lead (5 pin) to BS1363 (16 A)	1000-770
Calibration Certificate	1001-284	Barcode reader, USB	1001-047
Continuity/earth bond lead	1001-233	Barcode Label Printer (Brother P700) (USB)	1005-423
Extension lead adaptor BS1363	1001-234	USB cable	1004-610
Flash test lead	1007-165	Barcode printer label refills (cartridge)	90001-010
Carry case with lead/document pouch	2000-962	Appliance bar-code labels (1-1000)	6121-483
Plug adaptor IEC C6 - C13	1001-232	Roll of 1000 FAIL test labels	1001-227
		Roll of 1000 PASS test labels	1000-971
		PAT accessory pouch	2001-044
		PAT test certificate book	1001-299
		Screen protector (2)	1002-572

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T. +44 (0) 1304 502101
E. UKsales@megger.com

PAT400UK_DS_en_V10

www.megger.com
ISO 9001
The word 'Megger' is a registered trademark

Megger ^R

Les services d'EURO-INDEX

EURO-INDEX fournit des services pour tous les instruments de sa gamme de fournitures et offre des services, de la connaissance et du personnel hautement qualifié pour l'entretien (préventif), la réparation et le calibrage de vos instruments de mesure.

Centre de Service Agréé.....

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées.

Autrement dit, vos instruments sont traités par du personnel formé et compétent, qui dispose des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument ainsi que la certification (ATEX, EN50379, etc.) restent valables.

Laboratoire de maintenance et de calibrage

EURO-INDEX dispose d'un laboratoire de maintenance et de calibrage particulièrement moderne, titulaire d'une accréditation conforme à la norme NEN-EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105.



MQS®

MQS est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure. La prise en charge de multiples aspects vise à vous libérer de tout souci lors de l'utilisation de vos instruments de mesure. Les coûts sont modiques et prévisibles.

Accès numérique à vos certificats de calibrage avec Mon MQS

Mon MQS est un portail Web qui vous donne accès partout et à tout moment à vos certificats de calibrage et aux documents apparentés.

Location d'instruments de mesure

- Vaste assortiment
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires et leurs certificats de calibrage traçables

EURO-INDEX Academy

- Formations sur les produits (individuelles et collectives)
- Séminaires
- Vidéos de démonstration et d'instruction

Visionnez la vidéo sur notre chaîne YouTube et découvrez tout ce qu'il vous faut savoir sur MQS



Guichet des services



Calibrage de l'analyse de gaz de combustion



Séminaires et ateliers



Calibrage de la thermographie

Sous réserve de modifications EURO-INDEX® FR 18001

Le nom et la marque Bluetooth® sont la propriété de Bluetooth SIG Inc. L'utilisation de ce nom par EURO-INDEX s'effectue sous licence.



BELGIQUE
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

PAYS-BAS
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

