

## RCDT300 Series Residual Current Device Testers



- Tests standard, Type A, selective, and programmable RCDs.
- Ramp testing (RCDT320/330).
- Auto (Remote) testing (RCDT320/330).
- 3 Phase safe Enables testing on 110 V centre tapped supplies (RCDT320/330).
- Tough rubber armoured case with built-in cover.
- Weatherproof to IP54.
- USB interface for downloading test result (RCDT330).

### DESCRIPTION

#### Standard test ranges

- The RCDT300 series can perform 1/2I, 1I and 5I tests on RCDs rated at 30 mA, 100 mA, 300 mA and 500 mA on general and selective (time delayed) RCDs. The RCDT320/330 can also test RCDs rated at 10 mA and 1000 mA. All units offer Type A.

- Test times for normal and Selective RCDs are:

	Normal	Selective
1/2I	2 s	2 s
I	300 ms	2 s
5I	40 ms	150 ms

- 5I tests are available on RCDs rated up to 100 mA.

#### Polarity

- All RCDs can be tested at 0° or 180°

#### Selective RCDs (Type S)

- Selective breakers have a time delay in tripping. When selected, trip test times are extended and a 30s delay is allowed between the measurement of the fault voltage and the application of the test current.

#### Touch voltage

- Touch voltage is measured at the start of the RCD test. If enabled it is displayed on the analogue arc on completion of testing.

Touch voltage inhibit is selectable from 25 V or 50 V.

#### Tough:-

- Designed to take the bashing that testers receive on site, the Megger RCDT testers are rubber armoured.
- The rigid display cover folds right out of the way during testing and locks down to protect the display when it is finished.

#### Simple to use:-

- No buried functions mean it is obvious how to use the Megger RCDT.
- Colour coded ranges help test range selection, reducing test times and fault location.
- A user guide in the lid provides all the basic information.

#### Hands free use:-

- It hangs comfortably around the neck for hands-free use because the instrument is carefully balanced.

#### Type A (pulsed DC sensitive) RCD's

- Can be tested at 1/2I, 1I and 5I

#### Ramp testing (RCDT320/330)

- To measure the trip current of an RCD. Current level is slowly increased from 1/2I to 1I (+10%). When the RCD trips the trip current is displayed and held on the screen.
- Very useful diagnosing nuisance tripping of RCDs.

## RCDT300 Series Residual Current Device Testers

### Auto testing (RCDT320/330)

■ Where the RCD under test and tester need to be in different locations, the user connects the RCDT320/330 to the circuit and goes to standby the RCD under test to reset it. The RCDT320/330 will automatically perform a 1/2I, I and 5I test at both 0° and 180°. The RCD is reset each time it trips by the electrician and the tester proceeds to the next test automatically. All results are displayed at the end of the test, saving you time and energy

The RCDT330 adds the ability to test Programmable RCDs to the test options available, covering the range from 10 mA to 1000 mA, with step increments starting at 1 mA.

The RCDT330 additionally offers the facility to save test results to internal memory. Over 1000 result can be saved on site, and downloaded to a computer when convenient. Data is stored in non-volatile memory, being retained when the instrument is switched off or batteries are exhausted.

A Job reference number can be selected for a range of results, allowing separate locations to be tested with the same tester and easily separated when downloaded.

A memory bar graph acts as a 'Fuel Gauge' showing how much memory has been used.

Test results are downloaded to CSV (Comma Separated Variable) spreadsheets, and can be imported into Microsoft Excel. If certificates or reports are required, the results can be uploaded directly into Megger Certsuite ([Certsuite.app](#)) with a range of features for creating professionally finished documentation for NICEIC, ECA BS and other standard formats.

**Safety features:-** To protect the user and the tester from incorrect use the RCDT series all has an extensive range of features known as Megger Intelligent Safety System including:

- LED connection indicators – show test lead connections and supply status
- Safety Interlock – prevents unsafe connection of test leads
- 3 Phase safe - Even if the RCDT is connected across phases, the instruments will remain safe and not be damaged (RCDT320/330).
- Test inhibit – If supply voltage exceeds 300V testing will be inhibited.

All the Megger RCDT300 series RCD testers meet or exceed the UK and International Wiring Regulations, including requirements of BS7671 and VDE 0413 parts 1 and 4, HD 384, IEC 364, NFC15-100, and NEN3140, ES59009, AS/NZS 3000 and EN 61557.

In addition the range meets the requirements of IEC 61010-1 for safe connection to Category III supply (300 V Phase to Earth).

The new Megger electrician's testers are simple, no fuss electrical testers that are tough, reliable and easy to use. Available in separate instruments, the series consists of the:

- MIT300 range
- LT300 range
- RCDT300 range
- Insulation and continuity
- Loop testing
- RCD testing

Between them they meet all the requirements for modern electrical testing.

### SELECTION GUIDE

RCDT310 RCDT320 RCDT330

#### RCD testing

	RCDT310	RCDT320	RCDT330
Type AC RCD's			
1/2I, I, 5I RCD trip time test	■	■	■
Selective breakers (Type S)	■	■	■
Type AC RCD's			
1/2I, I, 5I RCD trip time test	■	■	■
30, 100, 300, 500 mA RCDs	■	■	■
10 mA /1 A RCDs		■	■
RCD trip current test (RAMP)		■	■
Auto sequence test		■	■
0°/180° polarity selection	■	■	■
Touch voltage display inhibit (selectable)	■	■	■
Max Touch voltage (25V/50 V)	■	■	■
Operating range 100 to 280 V	■		
Operating range 50 to 280 V		■	■

## RCDT300 Series Residual Current Device Testers

SELECTION GUIDE	RCDT310	RCDT320	RCDT330
Programmable RCDs			■
Frequency measurement		■	■
<b>Features</b>			
3 Phase Safe		■	■
Large clear display	■	■	■
Backlight		■	■
Battery status indication	■	■	■
Auto power down	■	■	■
Fuse blown indication	■	■	■
IP54 weatherproof	■	■	■
Result storage			■
Downloading			■
USB interface			■
IEC61010-1 CATIII 300 V	■	■	■
EN61557	■	■	■
Calibration Certificate	■	■	■
3 year warranty	■	■	■
<b>Accessories</b>			
Plug ended test lead	■	■	■
2 wire ended test lead probe/croc clip ended		■	■

### SPECIFICATION

#### RCD Test Ranges (to EN61557-6)

##### Supply voltage

Supply:	RCDT310 100 V - 280 V 45 Hz to 65 Hz
Hz	RCDT320 50 V - 280 V 45 Hz to 65 Hz
Hz	RCDT330 50 V - 280 V 45 Hz to 65 Hz
for	Minimum voltage 71 V for 300 mA RCDs, 100 V for 500 mA RCDs and 205 V 1000 mA RCDs

#### Test Current Accuracy:

No Trip Test:	(1/2I) -8% to -2%
Trip Test:	(I, 5I) +2% to +8%
Trip Time:	±1% ±1ms

#### Voltage measurement (All Models)

Range ac:	0 V - 300 V 25 Hz to 450 Hz
Accuracy:	±2% ±2 digits

#### Frequency measurement (RCDT320/330)

Range:	25 Hz to 450 Hz
Accuracy:	25.0 Hz to 199.9 Hz ±0.1 Hz 200 Hz to 450 Hz ±1 Hz

#### Fault (Touch) Voltage

Displayed range:	0 V to 50 V
Error:	+5%/+15% ±0.5 V

#### Programmable RCD step Increments

10 mA to 50 mA - 1 mA steps
50 mA to 500 mA - 5 mA steps
500 mA to 1000 mA - 10 mA steps

#### Test result storage (1000 results) (RCDT330)

Job Number	256 locations
Distribution Board no.	99 locations
Circuits	99 locations
Phases	P1, P2, P3

Last recorded result may be recalled to the display. All data can be downloaded to a PC using Download Manager (supplied) or Megger CertSuite software (Visit [Certsuite.app](http://Certsuite.app) for more information).

#### Temperature and humidity

Operating Range:	-5°C to +40°C
Operating Humidity:	93% R.H. at +40°C max.
Storage Range:	-25°C to +70°C
Maximum altitude:	2000m
Environmental Protection:	IP54

**Communications** USB interface

**Safety** Meets the requirements of IEC61010-1 Cat III 300 V phase to earth.

**IEC61557** Complies with the following parts of EN61557, Electrical safety in low voltage systems up to 1000 V ac and 1500 V dc- Equipment for testing, measuring or monitoring of protective measures: Part1-General Requirements Part4-Residual current devices

# RCDT300 Series

## Residual Current Device Testers

### Power supply

<b>Batteries:</b>	8 x 1,5 V cells IEC LR6 type (AA alkaline).
<b>Rechargeable:</b>	8 x 1.2 V NiCd or NiMH cells.
<b>Battery Life:</b>	2000 consecutive tests
<b>Weight</b>	All units 980 gms
<b>Dimensions</b>	All units 203 x 148 x 78 mm
<b>E.M.C.</b>	In accordance with IEC61326-1

### ORDERING INFORMATION

Description	Order Code	Description	Order Code
<b>UK</b>		<b>EUROPE</b>	
RCDT310 RCD Tester 30, 100, 300, 500 mA	RCDT310-EN-BS	RCDT310 RCD Tester 30, 100, 300,500 mA RCDT310-EN-SC	
RCDT320 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT320-EN-BS	RCDT320 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT320-EN-SC
RCDT330 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT330-EN-BS	RCDT330 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT330-EN-SC
<b>Included Accessories</b>		<b>Included Accessories</b>	
Mains plug test lead (BS1363)	6231-601	Schuko plug test lead (CEE 7/7)	1005-078
2-wire test lead with prods and clips (not RCDT310)	1001-976	2-wire test lead with prods and clips (not RCDT310)	1001-976
<b>AUSTRALIA</b>		<b>Optional Accessories for all RCDT's</b>	
RCDT310 RCD Tester 30, 100, 300, 500 mA	RCDT310-EN-AU	2-wire test lead with prods and clips	1014-294
RCDT320 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT320-EN-AU	Fused 2-wire test lead with prods and clips	1014-297
RCDT330 RCD Tester 10, 30, 100, 300, 500,1000 mA	RCDT330-EN-AU		
<b>Included Accessories</b>			
Mains plug test lead (AS/NZS 3112)	1005-080		
2-wire test lead with prods and clips (not RCDT310)	1014-294		

### SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T. +44 (0) 1304 502101  
E. UKsales@megger.com

### RCDT300\_DS\_en\_V11

www.megger.com  
ISO 9001  
The word 'Megger' is a registered trademark

**Megger** <sup>R</sup>

# Diensten van EURO-INDEX


EURO-INDEX is fabrikant van BLAUWE LIJN en importeur/distributeur van diverse A-merken test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX is van de meeste merken in het assortiment een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument blijft intact, net als de certificering (ATEX, EN50379, etc.).

## Kalibratielaboratorium

Ons service- en kalibratielaboratorium is BELAC-geaccrediteerd volgens de norm EN-ISO/IEC 17025. De accreditatie geldt voor grootheden en meetbereiken zoals vermeld in de gewaarmerkte bijlage met certificaatnummer [760-CAL](#).



## KWS®

KWS® is een kalibratieformule voor uw test- en meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Uw kalibratiecertificaten zijn digitaal beschikbaar via Mijn KWS (gratis webportaal en app) en door de QR-code te scannen op de kalibratiesticker van het instrument.

## Verhuur van meetinstrumenten

Er zijn diverse situaties waarbij huren handig is:

- U heeft tijdelijk extra toestellen nodig.
- Uw eigen meetinstrument wordt onderhouden en/of gekalibreerd.
- U moet een eenmalige meting verrichten.

## EURO-INDEX Academy

- Trainingen, infosessies en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Kalibratielaboratorium

Wijzigingen voorbehouden EURO-INDEX® VL 26001



BELGIË  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
[sales@euro-index.be](mailto:sales@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)

NEDERLAND  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)

