TDR1000/3P
Handheld TDR

- **Simple operation**
- **AUTO set up for instant use**
- **Ultra fast pulse for near end fault identification**
- **Trace HOLD feature to allow comparison between cables**
- **IP54 rating offers real life working**
- **Designed for use on all metallic cable pairs**

DESCRIPTION

The TDR1000/3P is a hand held, compact Time Domain Reflectometer for locating faults on metallic cables. It has a minimum resolution of 0.1 m/0.3 ft and a 5 km/15 kft maximum range depending on velocity factor selected and cable type.

Four output impedances are available (25, 50, 75, and 100 Ω) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements

The TDR1000 has a simple selection option which together with a 4 way control switch offers an intuitive operation for the user.

FEATURES AND BENIFITS

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. Dual cursors allow complete flexibility, giving the operator full control and instant indication of distance between two points.

A trace HOLD feature also allows comparison between conditions, something not seen on most other handheld TDRs. Extra high resolution together with white-light backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.

- Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 0.1 m
- For use on Telecom TNV-3 circuit, or 150 V CAT IV power circuits
- Power blocking filter not required
- Environmental protection to IP54
- Auto selected output impedance (between 25, 50, 75 and 100 Ω)
- 2 ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- Display distance in metres or feet
- Uses five AA (LR6) primary cells

SPECIFICATIONS

Range	10 m, 25 m, 100 m, 250 m, 1000 m, 2500 m, 5000 m (30 ft, 75 ft, 300 ft, 750 ft, 3000 ft, 7500 ft, 15000 ft)
Accuracy	±1% of range ± pixel at 0.67 VF

[Note- The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.]

Resolution	1% of range
Input protection	This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV when used with the supplied fused test lead set.
Output pulse	5 volts peak to peak into open circuit. Pulse widths determined by range and cable
Gain	Set for each range with three user selectable steps (in Manual operating mode)
Velocity factor	Variable from 0.2 to 0.99 in steps of 0.01
TX null	Automatic
Power down	Automatic after 5 minutes with no key press
Backlight	Stays on for 1 minute with no key press
Battery	Five LR6 (AA) type batteries, Manganese alkali or nickel metal-hydride cells
Battery life	Up to 14 hours (Typical)
Dimensions	230 x 115 x 48 mm (9.0 x 4.5 x 2.0 inches)
Weight	0.6 kg (1.32 lbs)
Case	ABS
Connectors	Two 4 mm-safety terminals
Test lead	(19 mm spaced TDR1000/3P): 1 pair 1.5 m retractable sheath, fitted with 500 mA FF HBC 1 kV 50 kA fuse
Display	256 x 128 pixel Graphics LCD
Operating temperature range and humidity	-15 °C to +50 °C (5 °F to 122 °F)
Storage temperature range and humidity	-20 °C to 70 °C (-4 °F to 158 °F)
Safety	When using the supplied fused test lead set this instrument complies with IEC61010-1 for connection to live systems with less than 300 V between the terminals and up to 150 V CAT IV to earth
EMC	Complies with Electromagnetic Compatibility Specifications (Light industrial) BS EN 61326-1, with a minimum performance of 'B' for all immunity tests

ORDERING INFORMATION

Description	Part number
Time Domain Reflectometer	1001-789

Description	Part number
Included accessories	
Hard case	
User guide CD	
Retractable sheath fused test lead (1 pair)	
Optional accessories	
Miniature clip test lead set (1 pair)	6231-652
Red and black probes and clips - for use with all Megger TDR Fused Test Leads.	1002-491
Split conductor fused test lead set (1 pair)	1002-015

SALES OFFICE
Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

TDR10003P_DS_en_V07
www.megger.com
ISO 9001
The word 'Megger' is a registered trademark

Megger

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.

Meer info

Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam “Mobiele Service”. Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

Meer info

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Meer info

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

Meer info

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo’s
- Application notes

Meer info

Servicebalie

Onderhoud, reparatie en kalibratie

Trainingen en seminars

Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001

EURO INDEX

BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

MANAGEMENTSYSTEEM CERTIFICATIE
DNV
ISO 9001