

Other instruments / adapters / accessories

MI 3143 EURO Z 440 V



The MI 3143 Euro Z 440 V is a multifunctional, portable battery (Li-ion) or mains powered test instrument with excellent IP protection: IP65 (case closed), IP54 (case opened). It can be controlled via an Android app aMESM, MI 3152, MI 3152H, MI 3155 or MI 3325. The MI 3143 Euro Z 440 V is intended for measuring the effectiveness of automatic trip out protection in case of faults in transformers and other HV equipment. With its high precision line and loop impedance measurements on AC circuits, high current dR 300A loop and line measurements for testing partial voltage drops and contact voltage measurement, it is ideal for testing in industrial settings.

KEY FEATURES

- **High precision 4-wire 220 A Z Line and Z Loop Impedance Tester;**
- **High range impedance measurements in 440 V / 16 ... 420 Hz AC Networks;**
- High current dR 300 A 4-wire **Partial Voltage drops;**
- **Ground Fault Analysis** with Contact, Touch and Step voltage;
- Floating voltmeter for partial contact results;
- **Selectable test load** (33.3 % to 100 %);
- Improved thermal performance;
- Portable battery (Li-ion) or mains powered test instrument;
- IP protection: IP65 (case closed), IP54 (case opened);
- **CAT IV 600 V (3000 m) safety category;**
- Bluetooth communication;
- **Black box design** (remote-controlled via an Android device).

APPLICATION

- Live Power Transformer Hi Precision 4-wire 300A Z Line / Loop Impedance Testing;
- Partial voltage drops resistances;
- High Current dR 300A Integrity of Grounding system;
- Earth Potentials by method of measuring Step, Touch and Transfer voltages;
- Automatic trip-out protection evaluation in case of faults in transformers, generators, turbines, contactors, distribution boards and switchyards whenever energetic loads and sources of protection exceed 200 A;
- Power transformer and motor winding measurement;
- Contact voltage measurement;
- High current injection ground fault simulation.

STANDARDS

Electromagnetic compatibility:

- EN 61326

Safety:

- EN 61010-1
- EN 61010-2-030
- EN 61010-031

Functionality:

- EN 61557
- IEEE 81-2012
- EN 60909-0

Li-ion battery pack:

- EN 62133-2

SUPPORTED INSTRUMENTS

- MI 3152 EurotestXC (Bluetooth, RS-232)
- MI 3152H EurotestXC 2.5kV (Bluetooth, RS-232)
- MI 3155 EurotestXD (Bluetooth, RS-232)
- MI 3325 MultiServiserXD (Bluetooth only)
- A 1522 aMESM as a console for performing tests

TECHNICAL SPECIFICATION

FUNCTION	Measuring range	Resolution	Accuracy
Impedance [Z]	0.1 mΩ ... 199.9 mΩ	0.1 mΩ	±(5 % of reading + 3 mΩ)
Z line mΩ	200 mΩ ... 1999 mΩ	1 mΩ	
Z loop mΩ	2.00 Ω ... 19.99 Ω	10 mΩ	±(5 % of reading + 3 digits)
Impedance [Z]	0.1 mΩ ... 199.9 mΩ	0.1 mΩ	±(5 % of reading + 3 mΩ)
High current ΔR	200 mΩ ... 1999 mΩ	1 mΩ	
	2.00 Ω ... 19.99 Ω	10 mΩ	±(5 % of reading + 3 digits)
Earth potential [U]	0.0 V ... 199.9 V	0.1 V	Calculated value
Utouch	200 V ... 999 V	1 V	
Earth potential [U]	1 mV ... 1999 mV	1 mV	±(2 % of reading + 2 digits)
Um	2.00 V ... 19.99 V	10 mV	
	20.0 V ... 199.9 V	0.1 V	

OPTIONAL ACCESSORIES























Photo	Order No.	Acc. description
	A 1620	Test lead 5 m, black
	A 1621	Test lead 20 m, black
	A 1527	Test lead 5 m, red, 1.5 mm ²
	A 1640	Test lead 20 m, red, 1.5 mm ²
	A 1608	Test lead 20 m, green
	A 1654	Test lead on a cable reel, 50 m, red, 2.5 mm ² , extendable
	A 1509	Test lead on a cable reel, 50 m, black, extendable
	A 1510	Test lead on a cable reel, 50 m, green, extendable
	A 1619	Test lead, 2-wire
	A 1593	Large Kelvin test clip
	A 1595	Large test crocodile, black
	A 1596	Large test crocodile, red

Photo	Order No.	Acc. description
	A 1013	Crocodile clip, black
	A 1064	Crocodile clip, red
	A 1014	Test probe, black
	A 1016	Test probe, red
	A 1530	G clamp
	A 1597	Human body resistance probe
	A 1022	Test rod
	A 1528	Professional current earth spike, 50 cm
	S 2053	Step voltage plates
	P 1101	BASIC to PRO license key upgrade for Metrel ES Manager

GENERAL DATA

Battery power supply: 7.2 V DC (4.4 Ah Li-ion)
 Battery charging time: typical 3.0 h (deep discharge)
 Mains power supply: 90 ... 260 V AC, 45 ... 65 Hz, 80 VA
 Over-voltage category: 300 V CAT II
 Protection classification: reinforced insulation
 Measuring category: 600 V CAT IV
 Pollution degree: 2
 Degree of protection: IP 65 (case closed), IP 54 (case open)
 Dimensions (w x h x d): 36 cm x 16 cm x 33 cm
 Weight: 6.5 kg (without accessories)

ORDERING INFORMATION



Picture of MI 3143 EU set

Standard set (MI 3143)

- Instrument MI 3143 Euro Z 440 V
- Mains cable
- RS232-PS/2 cable
- Test lead, 2-wire, 2 pcs*
- Crocodile clip, black, 2 pcs
- Crocodile clip, red, 2 pcs
- Test probe, black, 2 pcs
- Test probe, red, 2 pcs
- Metrel aMESM Android PRO P 1102-AND license key integrated in instrument
- Short instruction manual
- Calibration certificate
- Protective bag for accessories

* Replaced by 5 m and 20 m test leads in MI 3143 EU set.

Euro set MI 3143 (EU)

- MI 3143 ST
- Test lead 5 m, black, 2 pcs
- Test lead 5 m, red, 2.5mm², 2 pcs
- Test lead 20 m, red, 2.5mm²
- Test lead 20 m, black
- Test lead 20 m, green
- Large Kelvin test clip, 2 pcs
- G clamp
- Human body resistance probe
- Test rod, 2 pcs
- Step voltage plates, 2 pcs
- Soft carrying bag

METREL D.D.

Measuring and Regulation Equipment
 Manufacturer
 Ljubljanska 77, SI-1354 Horjul, Slovenia
 T +386 (0)1 75 58 200, F +386 (0)1 75 49 226
 metrel@metrel.si, www.metrel.si

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
 Subject to technical change without notice.

Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
info@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

