

# Multifunctional electrical installation tester

## MI 3152 EurotestXC



MI 3152 EurotestXC is an instrument from the new generation of Metrel's multifunctional measuring instruments. The already well known functions like complete installation safety testing according to IEC/EN 61557 and AUTO SEQUENCE testing of TN, TT and IT earthing systems are managed by a completely new user interface based on large colour touch screen display. A wide range of functions is included: from on-line voltage monitoring, phase sequence testing, varistor testing, earth resistance measurement, illuminance measurement and TRMS current measurement up to RCD tests, line and loop impedance tests, specific earth resistance measurements as well as ISFL measurements and the IMD tests.



### MEASURING FUNCTIONS

- Insulation resistance with DC voltage from 50 V to 1000 V;
- **Varistor test;**
- Continuity of PE conductors with 200 mA DC test current with polarity change;
- Continuity of PE conductors with 7 mA test current without RCD tripping;
- Line/Loop impedance combined also in one function **Z AUTO**;
- Loop impedance with Trip Lock RCD function;
- TRMS voltage and frequency measurements;
- Phase sequence;
- Power and THD measurement (up to the 12<sup>th</sup> harmonic);
- RCD testing (general and selective, type AC, A, F, B, B+, **MI RCD**, **EV RCD**, PRCD, PRCD-K, PRCD-S);
- Earth resistance (3-wire and 2-clamps method);
- Specific earth resistance with Ro-adapter (option);
- TRMS leakage and load currents (option);
- First fault leakage current (ISFL);
- Testing of Insulation Monitoring Devices (IMDs);
- Illumination (option);
- High resolution Loop impedance (mΩ) (option);
- **EVSE AUTO SEQUENCES and function inspections.**
- Determining location of cables (option);
- QR and/or barcode scanner support (option).

### KEY FEATURES

- **Predefined profile dependent AUTO SEQUENCES.**
- Predefined **Automatic tests:**  
Auto TT (U, Zln, Zs, Uc);  
Auto TN/RCD (U, Zln, Zs, Rpe);  
Auto TN (U, Zln, Zlpe, Rpe);  
Auto IT (U, Zln, Isc, Isfl, IMD).
- **Built-in help screens** for referencing on site.
- **Built-in fuse tables** for automatic evaluation of the line / loop impedance result.
- Monitoring of all 3 voltages in real-time.
- **Automatic polarity reversal** on continuity test.
- Automated RCD testing procedure.
- **Automated Impedance testing procedure (Z AUTO).**
- **Functional inspections.**
- **Measurement filtering according to the selected area group.**
- Built-in charger and rechargeable batteries as standard accessory.
- **BT communication with PC, Android tablets and smart phones** via built-in BT.
- PC SW **Metrel ES Manager** (structure and report creation, data upload/download).
- Optional **aMESM Android APP** (structure and report creation, data upload/download).

### APPLICATION

- Testing of TT, TN and IT systems;
- Testing of single and multiphase systems;
- Initial and periodic testing of domestic installations;
- Maintenance;
- Lightning installations;
- Medical installation testing;
- Fire brigades, military and police vehicles;
- Construction sites;
- Mobile Video/Audio, Concert Halls, Fair Playground;
- Electrical Vehicle Supply Equipment (EVSE) testing.

### STANDARDS

#### Functionality

- EN 61557; DIN 5032

#### Other reference standards for testing:

- IEC/EN/HD 60364-4-41;
- IEC/EN 61008; IEC/EN 61009;
- BS 7671; AS/NZ 3017

#### Electromagnetic compatibility (EMC):

- IEC/EN 61326-1

#### Safety

- IEC/EN 61010-1; IEC/EN 61010-031;
- IEC/EN 61010-2-030; IEC/EN 61010-2-032;



## TECHNICAL SPECIFICATION

Function		Measuring range	Resolution	Accuracy
CONTINUITY	Test Current 7 mA 2-wire	0.00 Ω ... 19.99 Ω	0.1 Ω	±(5 % of r. + 3 digits)
		20.0 Ω ... 1999 Ω	1 Ω	
	Test Current 200 mA 2-wire	0.00 Ω ... 19.99 Ω	0.01 Ω	±(3 % of r. + 3 digits)
INSULATION RESISTANCE	Test Voltage 50/100/250 V	20.0 Ω ... 199.9 Ω	0.1 Ω	±(5 % of r.)
		200.0 Ω ... 1999 Ω	1 Ω	±(5 % of r.)
	Test Voltage 500/1000 V	0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of r. + 3 digits)
		20.0 MΩ ... 99.9 MΩ	0.1 MΩ	±(10 % of r.)
RCD	RCD Uc	0.00 V ... 19.99 V	0.1 V	(-0%/+15 %) of r. ±10 digits (-0%/+15 %) of r.
		20.0 V ... 99.9 V		
	RCD (t), RCD I Ramp	0.00 ms ... 40.0 ms 0.0 V ... max.time	0.1 ms	±1 ms ±3 ms
IMPEDANCE	Zline L-L, L-N Ipsc	0.00 Ω ... 9.99 Ω	0.01 Ω	±(5 % of r. + 5 digits)
		10.0 Ω ... 99.9 Ω	0.1 Ω	
100 Ω ... 999 Ω		1 Ω		
1.00 kΩ ... 9.99 kΩ		10 Ω		
Zloop L-PE, IpfC	0.00 Ω ... 9.99 Ω	0.01 Ω	±(5 % of r. + 5 digits)	
	10.0 Ω ... 99.9 Ω	0.1 Ω		
	100 Ω ... 999 Ω	1 Ω		
	1.00 kΩ ... 9.99 kΩ	10 Ω		
VOLTAGE	TRMS	0 ... 550 V	1 V	±(2 % of r. + 2 digits)
	Frequency	0.00 Hz ... 9.99 Hz 10.0 Hz ... 499.9 Hz	0.01 Hz 0.1 Hz	±(0.2 % of r. + 1 digits)
CURRENT	TRMS, AC with A 1018	0.0 mA ... 99.9 mA	0.1 mA	±(5 % of r. + 5 digits)
		100 mA ... 999 mA	1 mA	±(3 % of r. + 3 digits)
		1.00 A ... 19.99 A	0.01 A	±(3 % of r.)
	TRMS, AC with A 1019	0.0 mA ... 99.9 mA	0.1 mA	Indicative
		100 mA ... 999 mA	1 mA	±(5 % of r.)
		1.00 A ... 19.99 A	0.01 A	±(3 % of r.)
TRMS, AC/DC with A 1391, range=40 A	0.00 A ... 1.99 A	0.01 A	±(3 % of r. + 3 digits)	
	2.00 A ... 19.99 A 20.0 A ... 39.9 A	0.01 A 0.1 A	±(3 % of r.) ±(3 % of r.)	
TRMS, AC/DC with A 1391, range = 300 A	0.00 A ... 19.99 A	0.01 A	Indicative	
	20.0 A ... 39.9 A 40.0 A ... 299.9 A	0.1 A 0.1 A	Indicative ±(3 % of r. + 5 digits)	
EARTH RESISTANCE	3 wire	0.00 Ω ... 19.99 Ω	0.01 Ω	±(5 % of r. + 5 digits)
		20.0 Ω ... 199.9 Ω	0.1 Ω	
		200.0 Ω ... 9999 Ω	1 Ω	
	2 clamp	0.00 Ω ... 19.99 Ω	0.01 Ω	±(10 % of r. + 10 digits)
20.0 Ω ... 30.0 Ω		0.1 Ω	±(20 % of r.)	
30.1 Ω ... 39.9 Ω		0.1 Ω	±(30 % of r.)	
Specific earth resistance		0.0 Ωm ... 99.9 Ωm	0.1 Ωm	±(5 % of r.) for Re 1 Ω ... 1999kΩ
		100 Ωm ... 999 Ωm	1 Ωm	±(10 % of r.) for Re 2 kΩ ... 19.99kΩ
		10.0 kΩm ... 99.9 kΩm	0.1 kΩm	±(20 % of r.) for Re > 20 kΩ
		100 kΩm ... 9999 kΩm	1 kΩm	
FIRST FAULT LEAKAGE CURRENT		0.0 mA ... 19.9 mA	0.1 mA	±(5 % of r. + 3 digits)
IMD TEST	Threshold indicative insulation resistance	5 ... 640 kΩ	5 kΩ	Indicative values, up to 128 steps
ILLUMINANCE	Type B	0.01 lux ... 19.99 lux	0.01 lux	±(5 % of r. + 2 digits)
		20.0 lux ... 199.9 lux	0.1 lux	
200 lux ... 1999 lux		1 lux		
2.00 klux ... 19.99 klux		10 lux		
Type C	0.01 lux ... 19.99 lux	0.01 lux	±(10 % of r. + 3 digits)	
	20.0 lux ... 199.9 lux	0.1 lux		
	200 lux ... 1999 lux	1 lux		
	2.00 klux ... 19.99 klux	10 lux		
GENERAL	Power supply	9 VDC (6x1.5 V battery or accu, size AA)		
	Overvoltage category	1000 V DC CAT II; 600 V CAT III; 300 V CAT IV		
	Protection class	double insulation		
	COM port	BT, USB, RS232		
	Weight	1.3 kg		
	Size (l x h x w)	230 x 103 x 115 mm		

### METREL D.D.

Measuring and Regulation Equipment Manufacturer  
Ljubljanska 77, SI-1354 Horjul, Slovenia  
T +386 (0)1 75 58 200, F +386 (0)1 75 49 226  
metrel@metrel.si, www.metrel.si

## ORDERING INFORMATION



### Standard set MI 3152 ST

- Instrument MI 3152 EurotestXC
- Plug commander, 1.5 m
- Test lead, 3 x 1.5 m
- Power supply adapter + 6 NiMH rechargeable batteries, type AA
- Test probe, 3 pcs (blue, black, green)
- Crocodile clip, 3 pcs (blue, black, green)
- Earth set 20 m
- RS232 - PS/2 cable
- USB cable
- Soft carrying bag
- Soft carrying neck belt
- Metrel ES Manager BASIC license\*
- Short instruction manual

### Euro set MI 3152 EU

- Instrument MI 3152 EurotestXC (set ST)
- Current clamp A 1018 (low range, leakage)
- Current clamp A 1019
- Metrel ES Manager PRO license\*

\*Metrel ES Manager can be downloaded free of charge from Metrel Web server.

## OPTIONAL ACCESSORIES

Photo	Order No.	Acc. description
	A 1143	Euro Z 290 A
	A 1199	Ro-adapter
	A 1191	Receiver R10K
	A 1018	Current clamp (low range, leakage)
	A 1019	Current clamp
	A 1110	Three phase adapter
	A 1111	Three phase adapter with switch
	A 1314 BLK	Plug commander
	A 1401 BLK	Tip commander
	A 1172	Luxmeter sensor, type B (PS/2)
	A 1173	Luxmeter sensor, type C (PS/2)
	A 1105	Barcode scanner
	A 1160	Fast charger for 8 AA batteries with a set of 6 NiMH bat., type AA
	S 2027	Earth test set, 3-wire, 50 m
	P 1101	BASIC to PRO licence key upgrade for Metrel ES Manager

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery. Subject to technical change without notice.

# Service van EURO-INDEX

EURO-INDEX verleent service op alle meetinstrumenten uit haar leveringspakket en biedt de faciliteiten, kennis en hoog gekwalificeerd personeel voor (preventief) onderhoud, reparatie en kalibratie van uw meetinstrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum.

Dit betekent dat uw instrumenten worden behandeld door goed opgeleid en kundig personeel, dat beschikt over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen gebruikt en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Service- en kalibratielaboratorium

EURO-INDEX beschikt over een bijzonder modern service- en kalibratielaboratorium met RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor verschillende grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



## KWS®

KWS is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie. Veel zaken worden voor u geregeld, zodat u zonder zorgen gebruik kunt maken van uw meetinstrumenten. De kosten zijn laag en voorspelbaar.

## Digitale toegang tot uw kalibratiecertificaten met Mijn KWS

Via het Mijn KWS webportal heeft u altijd en overal toegang tot uw kalibratiecertificaten en gerelateerde documenten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Deskundig advies
- Instrumenten worden geleverd met accessoirepakket en herleidbaar kalibratiecertificaat

## EURO-INDEX Academy

- Producttrainingen (individueel en klassikaal)
- Seminars
- Demonstratie- en instructievideo's

Bekijk de video op ons YouTube kanaal en ontdek alles over KWS



Servicebalie



Kalibratie rookgasanalyse



Seminars en workshops



Kalibratie thermografie

Wijzigingen voorbehouden EURO-INDEX® VL 18001

Het Bluetooth® woord- en beeldmerk zijn eigendom van Bluetooth SIG, Inc. Gebruik van deze merken door EURO-INDEX geschiedt onder licentie.



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

