

# Earth testers

## MI 3288 Earth Insulation Tester



MI 3288 Earth Insulation Tester is a portable, battery powered test instrument with excellent IP protection and designed for high altitude (300 V CAT III at 4000 m). It can measure earth resistance, specific earth resistance, earth potential, step and touch voltages, insulation resistance and continuity of protection conductors of various energetic and non-energetic objects. The MI 3288 Earth Insulation Tester also supports 4-wire earth resistance measuring method in combination with one clamp, two clamps earth resistance measurement, 4-wire specific earth resistance measurement and TRMS current measurement.

With the option to measure earth potential, step and touch voltage it is a truly versatile tester. It can even test the breakdown voltage of overvoltage protection devices. Among supported features is also the download of saved results to a PC with the help of Metrel ES Manager PC software to the computer for evaluation and report generation after testing.

### MEASURING FUNCTIONS

- Earth resistance 4 - pole;
- Selective earth resistance with 1 clamp;
- Specific earth resistance **Ro Wenner and Schlumberger method**;
- Earth resistance with 2 iron clamps;
- Earth potential;
- Step and touch voltage measurement with external P/S probe;
- **Insulation resistance with DC voltage from 50 V to 2500 V** and PI, DAR calculation;
- Varistor test 2,5 kV;
- Current measurements with clamps AC;
- TRMS voltage and frequency measurements;
- Low Ohm measurements with 7 mA and 200 mA DC test current.

### KEY FEATURES

- Possibility of performing all main types of earth measurements with a single instrument.
- Multi-frequency test signal for best noise immunity.
- Insulation range: wide range of insulation test voltages from 50 V to 2500 V, resistance measuring range up to 100 GΩ.
- Overvoltage category 600 V CAT II, 300 V CAT III; **at 4000 m above sea level**.
- 4.3" colour LCD display with touch screen.
- Programmable AUTO SEQUENCES.
- High degree of protection.
- **4-wire 200 mA DC** resistance measurement.
- Support for single or automated measurements.
- Built-in charger and rechargeable Li-ion batteries as standard accessory.
- **BT communication** with PC, Android tablets and smart phones via built-in BT.
- PC SW Metrel ES Manager for measurement pre and post processing: preparation of the test structure, result download, tree-view, table view and graphical view, storing and printing.

### APPLICATION

- Initial and periodic testing of domestic and industrial installations.
- Industrial areas, smaller buildings, mining facilities.

### STANDARDS

#### Safety

- EN 61010 - 1
- EN 61010 - 2 - 030 c
- EN 61010 - 2 - 032
- EN 61010 - 031

#### Functionality

- EN 61557 - 2
- EN 61557 - 4
- EN 61557 - 5

#### Electromagnetic compatibility

- EN 61326

#### Other reference standards

- IEC/EN/HD 60364
- AS/NZ 3018
- CEI 64.8
- HD 384
- BS 7671
- VDE 0413

## TECHNICAL SPECIFICATION

FUNCTION	Measuring range	Resolution	Accuracy
Insulation resistance Riso Un = 2,5 kV	0 kΩ ... 999 kΩ	1 kΩ	±(3 % of reading + 3 digits)
	1.00 MΩ ... 9.99 MΩ	0.01 MΩ	
	10.0 MΩ ... 99.9 MΩ	0.1 MΩ	
	100 MΩ ... 999 MΩ	1 MΩ	
	1.00 GΩ ... 9.99 GΩ	10 MΩ	
Continuity 200 mA of PE conductor with polarity change	0.020 Ω ... 1.999 Ω	0.001 Ω	±(5 % of reading + 3 digits) ±(15 % of reading + 1 digit) ±(1 % of reading + 2 digits)
	2.00 Ω ... 19.99 Ω	0.01 Ω	
	20.0 Ω ... 999.9 Ω	0.1 Ω	
	1.000 kΩ ... 1.999 kΩ	1 Ω	
	0.0 Ω ... 199.9 Ω	0.1 Ω	
Low resistance continuity measurement, test current 7 mA (continuous measurement)	200 Ω ... 1.999 kΩ	1 Ω	±(0,5 % of reading + 5 digits)
	2.00 kΩ ... 19.99 kΩ	10 Ω	
	20.0 kΩ ... 199.9 kΩ	100 Ω	
	200 kΩ ... 999 kΩ	1 kΩ	
	0.010 Ω ... 1.999 Ω	0.001 Ω	
2.00 Ω ... 19.99 Ω	0.01 Ω		
20.0 Ω ... 199.9 Ω	0.1 Ω		
200 Ω ... 999 Ω	1 Ω		
1.000 kΩ ... 1.999 kΩ	0.001 kΩ		
Earth resistance 4-wire method test frequency 55 – 164 Hz	2.00 kΩ ... 19.99 kΩ	0.01 kΩ	
	0.010 Ω ... 1.999 Ω	0.001 Ω	±(8 % of reading + 3 digits)
	2.00 Ω ... 19.99 Ω	0.01 Ω	
	20.0 Ω ... 199.9 Ω	0.1 Ω	
	200 Ω ... 999 Ω	1 Ω	
1.000 kΩ ... 1.999 kΩ	0.001 kΩ		
Earth resistance 4-wire method with one current clamp - Selective	2.00 kΩ ... 19.99 kΩ	0.01 kΩ	±(20 % of reading)
	0.010 Ω ... 1.999 Ω	0.001 Ω	
	2.00 Ω ... 19.99 Ω	0.01 Ω	
	20.0 Ω ... 199.9 Ω	0.1 Ω	
	200 Ω ... 999 Ω	1 Ω	
2-clamp earth resistance measurement	1.000 kΩ ... 1.999 kΩ	0.001 kΩ	±(5 % of reading + 2 digits) ±(10 % of reading + 2 digits) ±(20 % of reading)
	2.00 kΩ ... 19.99 kΩ	0.01 kΩ	
	0.00 Ωm ... 9.99 Ωm	0.01 Ωm	
	10.0 Ω ... 49.9 Ω	0.1 Ω	
	50 Ω ... 100 Ω	1 Ω	
Specific earth resistance Ro Wenner and Schlumberger method	200 Ωm ... 999 Ωm	1 Ωm	calculated value (consider uncertainty of 4 - pole measurement)
	1.000 kΩm ... 1.999 kΩm	0.001 kΩm	
	2.00 kΩm ... 19.99 kΩm	0.01 kΩm	
	20.0 kΩm ... 199.9 kΩm	0.1 kΩm	
	200 kΩm ... 999 kΩm	1 kΩm	
Earth potential - voltage	1.0 MΩm ... 1.99 MΩm	10 kΩm	±(1 % of reading + 3 digits)
	0.00 mV ... 99.99 mV	0.01 mV	
	100.0 mV ... 999.9 mV	0.1 mV	
	1.000 V ... 9.999 V	1 mV	
	10.00 V ... 49.99 V	10 mV	
Step and Touch	0.1 V ... 199.9 V 200 V ... 999 V	0.1 V 1 V	calculated value
Voltage TRMS	0.000 V ... 9.999 V	0.001 V	Range: 15 ... 99 Hz ±(0.5 % of reading + 3 digits)
	10.00 V ... 99.99 V	0.01 V	Range: 100 ... 399 Hz ±(1 % of reading + 3 digits)
	100.0 V ... 749.9 V	0.1 V	Range: 400 ... 1200 Hz ±(5 % of reading + 3 digits)
Voltage DC	0.000 V ... 9.999 V	0.001 V	±(0.5 % of reading + 3 digits)
	10.00 V ... 99.99 V	0.01 V	
	100.0 V ... 999.9 V	0.1 V	
Frequency	15.00 Hz ... 99.99 Hz	0.01 Hz	±(0.2 % of reading + 1 digit)
	100.0 Hz ... 999.9 Hz	0.1 Hz	
	1000 Hz ... 1200 Hz	1 Hz	
Current with A 1281 Current clamp	10 mA ... 749 mA	1 mA	±(2.5 % of reading + 3 digits)
	0.10 A ... 749 A	0.01 A	
	2.0 A ... 99.9 A	0.1 A	
	100 A ... 149 A	1 A	
	20 A ... 999 A	1 A	
Varistor Test	0.0 V ... 99.9 V	0.1 V	±(1 % of reading + 3 digits)
	100 V ... 999 V	1 V	
	1.00 kV ... 2.50 kV	10 V	

### GENERAL

Measuring category	300 V CAT IV; derated to 600 V CAT II; 300 V CAT III at 4000 m ASL
Protection class	Double insulation
COM port	BT, USB
Display	4.3" colour LCD display with backlight and touch screen
Degree of protection	IP 54
Power supply	7.2 V (4400 mAh Li-ion battery pack)
Size (l x h x w)	250 x 110 x 160 mm
Weight	1.6 kg

### METREL D.D.

Measuring and Regulation Equipment Manufacturer  
Ljubljanska 77, SI-1354 Horjul, Slovenia  
T +386 (0)1 75 58 200, F +386 (0)1 75 49 226  
metrel@metrel.si, www.metrel.si

## ORDERING INFORMATION



Picture of MI 3288 - 50 m set

### Standard set MI 3288

- MI 3288 Earth Insulation Tester
- Battery pack 7,2 V 4400 mAh
- Power supply adapter 12 V/3 A
- 2,5 kV test lead, 2 x 1,5 m
- Test lead, green, 1,5 m
- Test lead, 4 x 1 m
- Test probe, 2 pcs (red, black)
- Crocodile clip, 4 pcs (black, blue, green, red)
- Soft carrying bag
- Soft carrying neck belt
- USB cable
- PC SW Metrel ES Manager BASIC License
- Short instruction manual
- Instruction manual (on CD)
- Calibration certificate

### MI 3288 – 20 m

- MI 3288 ST
- Earth test set, 20 m (2 x test lead, 20 m; 2 x test lead, 4,5 m; 4 x earth test rod)

### MI 3288 – 50 m

- MI 3288 ST
- Earth test set, 50 m (2 x test lead, 50 m; 2 x test lead, 4,5 m; 4 x earth test rod)

## OPTIONAL ACCESSORIES

Photo	Order No.	Acc.	Description
	A 1568		8800 mAh battery pack
	A 1019		Current clamp
	A 1281		Current clamp
	A 1227		Flexible current clamp
	S 2122		Earth test set, 4-wire, 20 m
	S 2123		Earth test set, 4-wire, 50 m
	S 2053		Step voltage plates
	A 1597		Human body resistance probe
	P 1101		BASIC to PRO licence key upgrade for Metrel ES Manager

# Les services d'EURO-INDEX

EURO-INDEX fournit des services pour tous les instruments de sa gamme de fournitures et offre des services, de la connaissance et du personnel hautement qualifié pour l'entretien (préventif), la réparation et le calibrage de vos instruments de mesure.

## Centre de Service Agréé.....

EURO-INDEX est un Centre de Service Agréé pour toutes les marques représentées.

Autrement dit, vos instruments sont traités par du personnel formé et compétent, qui dispose des outils et logiciels adéquats. Seules des pièces d'origine sont utilisées et la garantie de votre instrument ainsi que la certification (ATEX, EN50379, etc.) restent valables.

## Laboratoire de maintenance et de calibrage .....

EURO-INDEX dispose d'un laboratoire de maintenance et de calibrage particulièrement moderne, titulaire d'une accréditation conforme à la norme NEN-EN-ISO/IEC 17025. Cette accréditation est valable pour différentes grandeurs, telles que spécifiées dans le champ d'application associé au numéro d'accréditation K105.



## MQS® .....

MQS est une formule d'entretien exclusive comportant un entretien et un calibrage périodiques de vos instruments de mesure. La prise en charge de multiples aspects vise à vous libérer de tout souci lors de l'utilisation de vos instruments de mesure. Les coûts sont modiques et prévisibles.

## Accès numérique à vos certificats de calibrage avec Mon MQS .....

Mon MQS est un portail Web qui vous donne accès partout et à tout moment à vos certificats de calibrage et aux documents apparentés.

## Location d'instruments de mesure .....

- Vaste assortiment
- Conseils avisés
- Les instruments sont livrés avec leurs accessoires et leurs certificats de calibrage traçables

## EURO-INDEX Academy .....

- Formations sur les produits (individuelles et collectives)
- Séminaires
- Vidéos de démonstration et d'instruction

**Visionnez la vidéo sur notre chaîne YouTube et découvrez tout ce qu'il vous faut savoir sur MQS**



Guichet des services



Calibrage de l'analyse de gaz de combustion



Séminaires et ateliers



Calibrage de la thermographie

Sous réserve de modifications EURO-INDEX® FR 18001

Le nom et la marque Bluetooth® sont la propriété de Bluetooth SIG Inc. L'utilisation de ce nom par EURO-INDEX s'effectue sous licence.



**BELGIQUE**  
Leuvensesteenweg 607  
1930 Zaventem  
T: 02 - 757 92 44  
F: 02 - 757 92 64  
info@euro-index.be  
www.euro-index.be

**PAYS-BAS**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: +31 - (0)10 - 2 888 000  
F: +31 - (0)10 - 2 888 010  
verkoop@euro-index.nl  
www.euro-index.nl

