

VARIOTEC® 460 Tracergas | The specialist for leak detection with tracer gas and hydrogen



LEAK DETECTION
made in Germany

VARIOTEC® 460 Tracergas



Rely on precision and safety

The **VARIOTEC® 460 Tracergas** was developed especially for leak detection on underground pipes by using tracer gas. It is characterised by an outstanding price to performance ratio.

- Precise:** The extraordinarily low cross sensitivity of the gas-sensitive semiconductor (SC) with regard to moisture and methane ensures an absolutely sure result and a resolution down to 0.1 ppm H₂.
- Functional:** Thanks to an innovative operating concept, a large display and simple menu structure, device operators can quickly get reliable results.
- Efficient:** In combination with the bell probe D80 you can achieve outstanding reaction times.
- Flexible:** The expanded measuring range of the thermal-conductivity sensor, up to 100 % vol. H₂ easily allows for further measuring tasks.
- Integrated:** Save your measurements and transmit the results using the USB interface on the computer.
- Mobile:** The 4 AA-size rechargeable batteries can be charged in just 3 hours and the operating time is at least 8 hours. As an alternative, you can use disposable batteries.
- Reliable:** Sewerin measuring devices are well known for their quality and durability.


A tried and tested method

Using tracer gas is a tried and tested method of pinpointing leaks. It can be used in gas and water distribution networks, pipelines in buildings, heating systems, pressurised communication cables, gas-filled high voltage power lines and landfill sites sealed with double membrane layers. It can also be used to test for leaks in industrial products such as pipes, pumps, engine blocks and airfoils.

Detecting gas leaks by tracer gas involves feeding a mixture of 95% nitrogen (carrier gas) and 5% hydrogen into the pipelines or other equipment/products being tested. The hydrogen escapes through the leak and is detected by the highly sensitive, specialised sensor.

The low amount of hydrogen (just 5%) means that this method is safe: the gas is incombustible as per ISO 10156 thanks to the use of nitrogen as the carrier gas. It is non-toxic, and therefore also permitted for use in drinking water networks, as well as non-corrosive.

Tracer gas is cheap and easy to obtain from technical gas or welding gas dealers. It is also environmentally-neutral and permeates all cover layers such as asphalt, concrete and other seal coats. Tracer gas always looks for the shortest route from the leak to the surface.



VARIOTEC® 460 Tracergas



Inspection above ground

With the **VARIOTEC® 460 Tracergas** and a bell or carpet probe you can measure the smallest concentrations of gas above a gas pipe laid in the ground, so you can reliably determine the discharge location above a leak on gas or water pipe lines.



Inspections in houses

Detect the smallest traces of gas in buildings and pinpoint the source of the gas, e.g. for leaks in internal, covered pipe systems.



Measuring in bar holes

In combination with a localisation probe you can measure the gas concentration in the ground. In this way, you can exactly pinpoint the suspected leak site.



Gas measurement

Ensure that the lines are either completely filled with or completely emptied of gas when commissioning or decommissioning hydrogen pipelines.

Applications

Application		Measuring range (H ₂)	Sensors
Inspection above ground		0.0 ppm – 5 % vol.	Gas-sensitive semiconductor Thermal conductivity sensor
Measuring in bar holes		0.0 % vol. – 100 % vol.	Thermal conductivity sensor
House		0.0 ppm – 5 % vol.	Gas-sensitive semiconductor Thermal conductivity sensor
Gas measuring		0.0 % vol. – 100 % vol.	Thermal conductivity sensor



Technical data

Dimensions

(W x D x H): approx. 148 x 57 x 205 mm

Weight: approx. 1000 g

Protection rating: IP54

Certificate: TÜV 07 ATEX 553353 X II2G Ex d e ib IIB T4 Gb
Basic device without leather bag for:
CH₄, C₃H₈, C₄H₁₀, tracer gas with max. 5 % H₂ in N₂
II2G Ex d e ib IIC T4 Gb
Basic device with leather bag for:
CH₄, C₃H₈, C₄H₁₀, tracer gas, H₂

Charging voltage: 12 V DC (max. 1 A)

Operating temperature: -20 °C – +40 °C

Storage temperature: -25 °C – +60 °C

Atmospheric pressure: 800 – 1100 hPa

Humidity: 5 – 90 % r.h., non-condensing

Interface: USB

Memory: 8 MB

Display: 320 x 240 pixels

Accessories that add value

- Bell probe D80, carpet probe, localisation probe
- Carrying case
- Test gas generator PGG H₂ for producing small amounts of hydrogen for function control of the “Inspection above-ground” and “House” application ranges.

Please contact us for a comprehensive quotation, including additional technical specifications and information on accessories.



Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Het laboratorium in Nederland beschikt over een RvA accreditatie naar EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105. RvA kalibratiecertificaten zijn internationaal geaccepteerd en is gelijkwaardig aan BELAC.



Mobiele Service

Naast de vaste kalibratielaboratoria in Zaventem en Capelle aan den IJssel beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.be) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen, seminars en workshops
- Demonstratie- en instructievideo's
- Application notes



Servicebalie



Onderhoud, reparatie en kalibratie



Trainingen en seminars



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® VL 23001



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: 02 - 757 92 44
F: 02 - 757 92 64
sales@euro-index.be
www.euro-index.be

NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: +31 - (0)10 - 2 888 000
F: +31 - (0)10 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl

